

# INTELLIGENT METER

Model : EM-9200

ISO-9001, CE, IEC1010



Type K Temp. probe  
TP-01, TP-02A, TP-03



Sound adapter, SL-407



Humidity probe, HD-200PRH



Anemometer HD-200PAL



Light adapter, HD-200PLX



LUTRON ELECTRONIC

*The Art of Measurement*

**Type K/J thermometer  
Humidity ( optional ), Anemometer ( optional )  
Light ( optional ) , Sound level measurement ( optional )**

# INTELLIGENT METER

**Model : EM-9200**

## FEATURES

* Intelligent instrument, multi-function, all in one.
* Meter build in Type K/J thermometer. Be plugged with optional " plug & play " probe HD-200PRH, HD-200PAL, HD-200PLX, SL-407 to be used as a professional Humidity/Temp. meter, Anemometer, Light meter, Sound level meter.
* Thermocouple Thermometer can default to accept type K or type J Temp. probe.
* Temperature measurement can default the display unit to °C or °F.
* Anemometer can default the display unit to m/S, FPM, Km/h, mph, knot.
* Light meter can default the display unit to LUX or Ft-cd.
* Meter can default auto power off or manual power off.
* 0.1 degree resolution for temperature measurement.
* Microcomputer circuit provides intelligent function and high accuracy.
* LCD with two display, easy readout.
* Records Maximum and Minimum readings with recall. Data hold function for freezing the desired value.
* Build in the input socket for DC 9V power adapter.
* RS232 PC serial interface.
* Few panel buttons, easy operation.
* Built-in low battery indicator.
* Heavy duty & compact housing case.
* Available for the HVAC applications.

## GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.
Display	* LCD size : 60 mm x 33 mm * Dual function meter's display.
Measurement	* Type K/J thermometer ( optional probe ). * Humidity/Temp. meter ( optional probe ). * Anemometer with Temp. ( optional probe ). * Light meter ( optional probe ). * Sound level meter ( optional adapter ).
Temperature Compensation	Automatic cold junction compensation both type K/J thermometer * Type K/J Temp.
Linear Compensation	Linear Compensation for the full range. * Type K/J Temp.
Input Socket	Standard 2 pin thermocouple socket. * Type K/J Temp.
Over Indication	Show " - - - - - ".
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Sampling Time of display	Approx. 1 second.
Power off	Auto shut off to save battery life or manual off by push button.
Data Output	RS 232 PC serial interface.
Operating Temperature	0 to 50 °C.
Operating Humidity	Less than 80% R.H.
Power Supply	006P DC 9V battery ( Alkaline or Heavy duty type ). DC 9V adapter input. * AC/DC power adapter is optional.
Power Current	Type K/J thermometer : Approx. DC 6 mA Humidity, Anemometer, Light meter : Approx. DC 10 mA
Weight	256 g/0.56 LB, main instrument.
Dimension	180 x 72 x 32 mm * meter 7.1 x 2.8 x 1.3 inch
Accessories Included	Instruction manual..... 1 PC Carrying case..... 1 PC

Optional Accessories	* Type K thermocouple probe. TP-01, TP-02A, TP-03, TP-04. * Humidity probe, HD-200PRH * Anemometer probe, HD-200PAL * Light probe, HD-200PLX * Sound adapter, SL-407 * AC to DC 9V adapter. * RS232 cable, UPCB-02. * USB cable, USB-01 * Data Acquisition software, SW-U801-WIN. * Carrying case, CA-05A, CA-06.
----------------------	--

## ELECTRICAL SPECIFICATIONS (23±5 °C)

### Type K/J Thermometer

Sensor Type	Resolution	Range	Accuracy
Type K	0.1 °C	-50.0 to 1300.0 °C	± ( 0.4 % + 0.8 °C )
		-50.1 to -199.9 °C	± ( 0.4 % + 1 °C )
	0.1 °F	-58.0 to 2372.0 °F	± ( 0.4 % + 1.5 °F )
		-58.1 to -327.8 °F	± ( 0.4 % + 1.8 °F )
Type J	0.1 °C	-50.0 to 1100.0 °C	± ( 0.4 % + 0.8 °C )
		-50.1 to -199.9 °C	± ( 0.4 % + 1 °C )
	0.1 °F	-58.0 to 2012.0 °F	± ( 0.4 % + 1.5 °F )
		-58.1 to -327.8 °F	± ( 0.4 % + 1.8 °F )

\* Accuracy value is specified for the meter only.

\* Temp. probe ( Type K, TP-01 TP-02A, TP-03, TP-04 ) is the optional accessories, refer page 22.

### Anemometer ( optional probe, HD-200PAL )

#### A. Air velocity

Measurement	Range	Resolution	Accuracy
m/S	0.4 - 25.0 m/s	0.1 m/s	± (2% + 0.2 m/s)
km/h	1.4 - 90.0 km/h	0.1 km/h	± (2% + 0.8 km/h)
mph	0.9 - 55.9 mile/h	0.1 mile/h	± (2% + 0.4 mile/h)
knot	0.8 - 48.6 knots	0.1 knots	± (2% + 0.4 knots)
FPM	80 - 4930 ft/min	1 ft/min	± (2%+40 ft/min.)

Note: m/S - meters per second      km/h - kilometers per hour  
FPM - feet/per minute      knot - nautical miles per hour  
mph - miles per hour      (international knot)

#### B. Temperature

Measuring Range	0 °C to 50 °C/32 °F to 122 °F
Resolution	0.1 °C/0.1 °F
Accuracy	± 0.8 °C/1.5 °F

### Humidity/Temp. meter ( optional probe, HD-200PRH )

#### A. Humidity

Measuring Range	0 % to 95 % R.H.
Resolution	0.1 % R.H.
Accuracy	≥ 70% RH      ± (3% reading + 1% RH). < 70% RH      ± 3% RH.

#### B. Temperature

Measuring Range	0 °C to 50 °C/32 °F to 122 °F
Resolution	0.1 °C/0.1 °F
Accuracy	± 0.8 °C/1.5 °F

### Light meter ( optional probe, HD-200PLX )

Measuring Range	LUX	0 to 20,000 LUX.
	Ft-cd	0 to 2,000 Ft-cd
Resolution	LUX	1 LUX
	Ft-cd	0.1 Ft-cd
Accuracy	± ( 5% rdg ± 8 dgt )	

Note: Ft-cd : Feet candle