

Regulator & Pressure Gauge



**Regulator
ZR-2017BT**



**Regulator
ZR-2018BB**



**Pressure Gauge
ZR-2020BBP**

Standard	EN 16129	EN 16129	EN 16129
Flow Capacity	1.5 kg/h	1.5 kg/h	1.5 kg/h
Nozzle Size	13 mm	13 mm	13 mm
Weight	0.34 kg	0.24 kg	0.34 kg
Pin Type	Plastic Spindle	Brass Spindle	Brass Spindle
Inlet Diameter	20 mm	20 mm	20 mm
Output Pressure	30 mbar / 3 kPa	30 mbar / 3 kPa	30 mbar / 3 kPa
Thermic Valve	Yes	-	-

Benefits

- **Features** : European standard
- **Pressure Gauge** : To monitor the use of gases in cylinders and test gas leak (Refer to model ZR-2020BBP)
- **Pressure** : Low pressure regulator for LP gas only
- **Body** : Compact
- **Excess flow protection device** : The gas flow will automatically cut-off when a sudden increase in gas pressure is detected. This may happen if the gas hose disconnects or ruptures.
- **Child safety lock** : Once the regulator is mounted on to the gas cylinder's valve, it is not easily removed. To remove the regulator, turn it off then press the release button to disconnect from the valve.
- **Diaphragm** : Reinforced rubber material to withstand excess pressure
- **Pin type** : Durable brass spindle (Refer to model ZR-2018BB & ZR-2020BBP)
- **Pin type** : The thermic valve will melt at 150°C to break off the gas supply from gas cylinder to gas cooker (Refer to model ZR-2017BT)
- **Warranty** : One year warranty in the event of a manufacturing defect

Regulator Pack:

Zenne (BS3212) LPG Hose (Standard Length : 1.5 meter)
Stainless Steel Hose Clip (2pcs)



All 3 models are available in pack