

## PERFORATED SHEET - SPECIFICATIONS

THICKNESS (mm)	HOLE (mm)	PITCH (mm)	Aperture (%)	MATERIAL
0.4	0.5	1	22.67	SS
0.5	3	5	32.65	GI
0.7	0.8	2	14.51	SS
0.7	3	5	32.65	GI,SS
0.9	3	5	32.65	SS
1.0	1	2	22.67	GI,SS
1.0	1.5	3	22.67	SS
1.0	2	3.5	29.61	GI,SS
1.0	3	5	32.65	GI,SS
1.0	5	8	35.43	GI,SS
1.0	6	9	40.31	GI,SS
1.0	8	12	40.31	GI,SS
1.0	10	15	40.31	GI,SS
1.2	3	5	32.65	GI,SS
1.2	5	8	35.43	GI,SS
1.2	6	9	40.31	GI,SS
1.2	8	12	40.31	GI,SS
1.5	2	3.5	29.61	GI,SS
1.5	3	5	32.65	GI,SS
1.5	5	8	35.43	GI,SS
1.5	8	12	40.31	GI,SS
1.5	10	15	40.31	GI,SS
2.0	2	4	22.67	GI,SS
2.0	3	5	32.65	GI,SS
2.0	5	8	35.43	GI,SS
2.0	6	9	40.31	GI,SS
2.0	8	12	40.31	GI,SS
2.0	10	15	40.31	GI,SS
2.0	13	18	47.31	GI
3.0	3	5	32.65	GI,SS
3.0	5	8	35.43	GI,SS
3.0	6	9	40.31	GI,SS
3.0	8	12	40.31	GI,SS
3.0	10	15	40.31	GI,SS

SS - Stainless Steel

GI - Galvanised