

Stainless Steel Open Burner

Table Top



Approved from Standard and Industrial Research Institute of Malaysia (2001 MA 0669)

ANSI Z 83.11:1996

ANSI = American National Standard Institute



OB 2S




OB 2




OB 4




OB 6




Side View




Front View




Side View



Front View



Front View



Front View

Free Standing



OB 2SFS




OB 2FS




OB 4FS




OB 6FS




Side View




Front View




Side View



Front View



Front View



Front View

- Full stainless steel constructed body, hygienic and easy to keep clean.
- Removable cast iron top grate.
- Drip pan is easily to removable and cleaning.
- Free standing designed
- Even heat high input 20,000 Btu burners or 21.00 MJ.
- Precision brass valving.
- Automatic piezo ignitor.
- Stand by manual lighting holes.

Model	Product Dimension (L x W x H) (mm)	Packing Dimension (L x W x H) (mm)	Weight (kg)	Gas Consumption Btu/Hr (MJ/Hr)	Packing Volume (m ³)	Number Of Burner
OB2S	600 x 417 + 60 x 350	700 x 530 x 420	28	40,000 (42.4)	0.16	2
OB2	300 x 720 + 60 x 350	350 x 780 x 400	28	40,000 (42.4)	0.11	2
OB4	600 x 720 + 60 x 350	777 x 677 x 400	48	80,000 (84.4)	0.21	4
OB6	900 x 720 + 60 x 350	953 x 770 x 400	70	120,000 (127.20)	0.29	6
OB2SFS	600 x 417 + 60 x 860	700 x 530 x 420	35	40,000 (42.4)	0.16	2
OB2FS	300 x 720 + 60 x 860	350 x 780 x 400	35	40,000 (42.4)	0.11	2
OB4FS	600 x 720 + 60 x 860	777 x 677 x 400	56	80,000 (84.4)	0.21	4
OB6FS	900 x 720 + 60 x 860	953 x 770 x 400	79	120,000 (127.20)	0.29	6