

RICOH

MP 2001SP/2501SP



MP 2001SP

20 ppm B/W

MP 2501SP

25 ppm B/W

GENERAL

Warm-up time:	20/20 seconds
First output time:	6/6 seconds
Continuous output speed:	20/25 pages per minute
Memory:	Standard: 1GB Maximum: 1.5GB
HDD:	Option: 250GB
Dimensions (WxDxH):	587 × 685 × 460/ 587 × 685 × 558 mm
Weight:	38/55 kg
Power source:	220V-240V, 50/60Hz

COPIER

Copying process:	Laser beam scanning and electro photographic printing
Multiple copying:	Up to 999 copies
Resolution:	600 dpi
Zoom:	From 50 to 200%

PRINTER

Printer language:	Standard: PCL5e, PCL6, XPS Option: Adobe® PostScript® 3™
Resolution:	600 x 600 dpi
Interface:	Standard: USB 2.0, SD slot, USB host interface, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X v10.5 or later
UNIX environments:	UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX: 10.x, 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4,5,6 IBM® AIX: 5L v5.3, 5L v6.1, 5L v7.1 IBM® System i5™ HPT
Novell environments:	v6.5
SAP® R/3® environments:	SAP® R/3®

SCANNER

Scanning speed:	Full colour: Maximum 50 originals per minute B/W: Maximum 50 originals per minute
Resolution:	Maximum: 600 dpi, 1,200 dpi (TWAIN)
Original size:	A3, A4, A5
File Format:	TIFF, JPEG, PDF, Encrypt PDF, High compression PDF, PDF-A
Bundled drivers:	Network TWAIN, Scanner utility
Scan to email:	SMTP, POP, IMAP4
Scan to folder:	SMB, FTP, NCP (Option)

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	7.7 x 3.85 line/mm, 200 x 100 dpi
Transmission speed:	G3: Approx. 2 seconds (200 x 100 dpi, JBIG) Approx. 2 seconds (200 x 100 dpi)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2 second(s)
Memory capacity:	Standard: 4MB

PAPER HANDLING

Recommended paper size:	Paper tray(s): Minimum (A5) Maximum (A3) Bypass tray: Minimum (A6) Maximum (A3)
Paper input capacity:	Maximum: 1,350/1,600 sheets
Paper output capacity:	Maximum: 350 sheets
Paper weight:	Paper tray(s): 60-105 g/m ² Bypass tray: 60-162 g/m ² Duplex unit: 64-90 g/m ²

ECOLOGY

Power consumption:	Maximum: 1,550 W Ready mode: 113 W Sleep mode: 0.6 W TEC (Typical Electricity Consumption): 892/1,082 W/h
---------------------------	---

OPTIONS

ADF handle, Platen cover, ARDF, 1 x 500-sheet paper tray, 2 x 500-sheet paper tray, One-bin tray, Hard disk drive, RAM, VM card, Netware, Browser unit, Adobe® PostScript® 3™ option, Counter interface, File format converter, Copy data security unit, Wireless LAN (IEEE 802.11a/g), IEEE 1284, Bluetooth, Fax option, Fax connection unit, Fax marker

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.