
























# Flexi-Filter® Pads for Advantage Respirators

These low-profile, flexible pads fit well under a welding hood and with other personal protective equipment. They offer great balance and weight distribution for maintaining a good face seal, while their swept-back design provides improved vision and comfort.

Filter Type & Efficiency  
See Definitions below

MSA Filter Description	Part No.	Color Coding	P100	R95	N95	See Notes below
Flexi-Filter P100	818342					1,4
Flexi-Filter P100 w/Nuisance Level OV, Ozone Removal	818343					1,4
Flexi-Filter P100 w/Nuisance Level AG, HF Removal	818344					1,4
Flexi-Filter N95	818346					1
Flexi-Filter N95 w/Nuisance Level OV Removal	818347					1
Flexi-Filter P95	818354					1
Flexi-Filter P95 w/Nuisance Level OV Removal	818355					1
Flexi-Filter P95 HF Removal (NIOSH)	10063227					1

### Definitions

**N95-Particulate Filter (95% filter efficiency level)** effective against particulate aerosols free of oil; time use restrictions may apply.

**R95-Particulate Filter (95% filter efficiency level)** effective against all particulate aerosols; time use restrictions may apply.

**P100-Particulate Filter (99.97% filter efficiency level)** effective against all particulate aerosols.

### Notes

1. Do not use in atmospheres containing less than 19.5 percent oxygen, in atmospheres containing gases or vapors or in atmospheres immediately dangerous to life and health.
2. Do not use in atmospheres containing less than 19.5 percent oxygen, or in atmospheres immediately dangerous to life and health.
3. Do not wear for protection against organic vapors with poor warning properties or those which generate high heats of reaction with the sorbent material in the cartridge.
4. 99.97 percent efficient against 0.3 micron DOP.

