



Vacuum truck hose, heavy and reinforced, very flexible

Application

- ♦ suction excavator
- ♦ municipal vehicle: sweeper, sweeping machine

Properties

- ♦ heavy duty and reinforced
- ♦ highly abrasion resistant
- ♦ microbe resistant
- ♦ good resistance to oil, gasoline and chemicals

- ♦ very good low temperature flexibility
- ♦ conforms to RoHS guideline
- ♦ REACH according to --> Technology / Technical Information / REACH

Temperature Range

- ♦ -40°C to 90°C
- ♦ short time to 125°C

Design

- ♦ AIRDUC® profile hose

- ♦ spring steel wire firmly embedded in wall
- ♦ wall: special premium polyurethane (Pre-PUR®)
- ♦ wall thickness 2,5 mm approx.
- ♦ reinforcement of the primary abrasion areas

Delivery variants

- ♦ further diameters and lengths available on request
- ♦ orange (standard)
- ♦ special colours: transparent, full coloured
- ♦ customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
8 / 200-203	213.00	0,600	0,120	316.00	5.13	-	5	355-0200-5202

Accessories



CONNECT 240 + 241 AS



CLAMP 211



CONNECT 270-271