

Vacuum cleaner hose, electrically conductive $<10^6 \Omega$

Application

- ♦ flexible hose/ ducting for gases and for dust, powder, fibres
- ♦ industrial vacuum cleaners, vacuum cleaners
- ♦ explosion hazard area
- ♦ swimming pool cleaning
- ♦ scrubber, floor cleaning machine

Properties

- ♦ light weight

- ♦ highly flexible
- ♦ crush resistant
- ♦ floatable
- ♦ good resistance to alkalis and acids
- ♦ surface resistance $<10^6$
- ♦ in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- ♦ conforms to RoHS guideline
- ♦ REACH according to --> Technology / Technical Information / REACH

Temperature Range

- ♦ -25°C to 65°C

Design

- ♦ EVA design
- ♦ self-supporting profile design
- ♦ open profile geometry
- ♦ wall: EVA

Delivery variants


- ♦ further diameters and lengths available on request
- ♦ black (standard)

I.D. (in / mm)	outer Ø (mm)	Vacuum (bar)	Bending Radius (mm)	Weight (kg/m)	Dimensions in Stock (m)	Production Lengths (m)	Order No.
1 / 25	32.20	0,500	54.00	0.15	30	-	373-0025-1003
1,25 / 32	40.40	0,500	66.00	0.24	30	-	373-0032-1003
1,5 / 38	47.20	0,500	74.00	0.31	30	-	373-0038-1003
- / 40	49.40	0,500	80.00	0.32	30	-	373-0040-1003
2 / 50-51	59.00	0,500	97.00	0.44	30	-	373-0050-1003

Accessories



CLAMP 208



CONNECT 228



CONNECT 227