



Vacuum cleaner hose

**Application**

- ♦ flexible hose/ ducting for gases and for dust, powder, fibres
- ♦ industrial vacuum cleaners, vacuum cleaners
- ♦ swimming pool cleaning
- ♦ scrubber, floor cleaning machine

**Properties**

- ♦ light weight

- ♦ highly flexible
- ♦ crush resistant
- ♦ floatable
- ♦ good resistance to alkalis and acids
- ♦ conforms to RoHS guideline
- ♦ REACH according to --> Technology / Technical Information / REACH

**Temperature Range**

- ♦ -45°C to 65°C

**Design**

- ♦ EVA design
- ♦ self-supporting profile design
- ♦ open profile geometry
- ♦ wall: EVA

**Delivery variants**

- ♦ further diameters and lengths available on request
- ♦ grey (standard)

I.D.	outer Ø	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	(m)	
- / 20	26.80	0,500	42.00	0.13	-	30	373-0020-0000
1 / 25	32.20	0,500	54.00	0.15	-	30	373-0025-0000
- / 30	38.00	0,500	62.00	0.20	-	30	373-0030-0000
1,25 / 32	40.40	0,500	66.00	0.24	<b>30</b>	-	373-0032-0000
1,36 / 35	43.80	0,500	71.00	0.26	-	30	373-0035-0000
1,5 / 38	47.20	0,500	74.00	0.31	<b>30</b>	-	373-0038-0000
- / 40	49.40	0,500	80.00	0.32	-	30	373-0040-0000
1,75 / 44-45	55.00	0,500	89.00	0.37	<b>30</b>	-	373-0045-0000
2 / 50-51	60.40	0,500	97.00	0.44	<b>30</b>	-	373-0050-0000
2,36 / 60	72.00	0,500	113.00	0.67	-	30	373-0060-0000

Accessories



CLAMP 208



CONNECT 228



CONNECT 227

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx.