



PTFE hose/ tubing

#### Application

- ♦ flexible hose/ ducting for liquids and
- ♦ for gases food industry, pharmaceutical industry: foodstuff, pharmaceutical
- ♦ heating hose: interior hose for media transfer

#### Properties

- ♦ highly flexible
- ♦ food grade wall, complies with: FDA 21 CFR Part 177.1550, German guideline XV BfR

- ♦ odourless and
- ♦ tasteless anti-
- ♦ adhesive
- ♦ microbe and hydrolysis
- ♦ resistant good resistance to
- ♦ alkalis and acids
- ♦ extremely good resistance to chemicals conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

#### Temperature Range

- ♦ -150° C to 200° C

#### Design

- ♦ NORFLEX design
- ♦ wall interior and exterior
- ♦ smooth wall: PTFE

#### Delivery variants

- ♦ further diameters and lengths available on request
- ♦ transparent (standard)

I.D.	outer Ø	Wall Thickness	Pressure	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	mm	(bar)	(kg/m)	(m)	
- / 2	4.00	1.00	15,000	0.01	<b>50</b>	407-9020-0000
1/8 / 3	5.00	1.00	15,000	0.01	<b>50</b>	407-9030-0000
- / 4	6.00	1.00	10,000	0.02	<b>50</b>	407-9040-0000
1/4 / 6	8.00	1.00	10,000	0.02	<b>50</b>	407-9060-0000
5/16 / 8	10.00	1.00	5,000	0.03	<b>50</b>	407-9080-0000
3/8 / 10	12.00	1.00	5,000	0.04	<b>50</b>	407-9100-0000
- / 12	14.00	1.00	5,000	0.04	<b>50</b>	407-9120-0000
- / 14	16.00	1.00	5,000	0.05	<b>50</b>	407-9140-0000

## Accessories



CLAMP 208