
NORPLAST® PVC 389 SUPERELASTIC WEAR STRIP (XHD)







PVC hose, super-heavy, flexible at low temp. (down to -25°C)

Application

- hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- suction vehicle: sewer cleaning, sewage cleaning
- vacuum truck, suction vehicle, dry suction truck: industrial cleaning, furnace cleaning
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: toilet discharging/ disposal
- agricultural industry: irrigation, fertilizers, insecticides
- agricultural industry: manure spreader, slurry spreader, slurry tanker
- silos and tankers: silo charging, silo discharging
- silo and tankers: conveying of wood pellets, plastic granulate, plastic powder

Properties

- external abrasion protection via external helix (protects floors and surfaces, prolongs service life, easy to use)
- super-heavy duty
- very high pressure, vacuum and compression resistance
- · good resistance to alkalis and acids
- good resistance to chemicals
- · very good low temperature flexibility
- · conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

• -25°C to 60°C

Design

- NORPLAST full plastic hose
- · outer hard plastic spiral
- abrasion resistant protection profile (wear strip)
- spiral: rigid PVC
- · smooth interior
- wall: high grade low temperature flexible soft PVC

Delivery variants

- further diameters and lengths available on request
- grey and blue partially coloured (standard)
- · special colours: coloured spiral, full coloured
- · customer-specific branding

	I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in	ı / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
3/	75-76	87.00	2,000	0,900	222.00	1.66	-	25 50	389-0076-1012
3,5	/ 89-90	103.00	1,700	0,900	270.00	1.96	-	10 30	389-0090-1012
4/	100-102	116.00	1,500	0,850	294.00	2.72	-	10 30	389-0102-1012
6/	150-152	170.00	1,000	0,600	449.00	4.08	-	10 20	389-0152-1012

Accessories



CONNECT KARDAN 254



CONNECT KAMLOK ALU 253



CONNECT 270-27



CLAMP 21