

PRODUCT

Eightfold Sdn Bhd (775128-W)
69-1, Jalan SS19/6, 47500 Subang Jaya,
Selangor Darul Ehsan, Malaysia
Tel: 03-5612 8169 Fax: 03-2726 8806
www.eightfold.com.my



NEXUS CALL SYSTEM



The spread of coronavirus has led to a significant surge in demand for medical ward services. In order to cope with bed short of the expected surge in corona patients, hospitals have already begun to step up and provide overflow bed capacity, and the call bell is an indispensable part of it. The **Nexus Call System** from Rondish may come in handy. It is a portable nurse call solution that can be quickly deployed with minimum installation. It's high flexibility making it a perfect choice for a surge in bedding needs during the coronavirus pandemic.

Features Highlight

- Color Coded Touchscreen Display
- Audio Call Levels Indication
- Calls Display in Order of Priority
- Multiple Call Devices are Available for Option
- Low Battery Alert
- Event Log and Response Time Tracking
- Password Protected
- Options for Wall-mount / Desk-mount



PRODUCT

Eightfold Sdn Bhd (775128-W)
69-1, Jalan SS19/6, 47500 Subang Jaya,
Selangor Darul Ehsan, Malaysia
Tel: 03-5612 8169 Fax: 03-2726 8806
www.eightfold.com.my



Wireless Design

Trim your construction cost with no wire, no conduit



Total Flexibility

Allow user to relocate or add extra equipment if required.



Indicator Light

Provide visual and distinctive audible alarm



Alert

Real time alert and response time tracking



Report

Event data collection and tracking



Password

Password protected login with admin and user access level



1 Bedhead Call Point With Integral Reset Button



2 Wireless Handset



3 Indicator Light & Signal Extender



4 PC Tablet To Display Alert Notifications

NDP-11 Nexus Display Panel



Optional



Bedhead Call Point With Handset



Fall Detection Pendant

NDP-11 Basic Info



- 10" Android tablet with folio included
- Customizable descriptions for device location
- Three alarm priority levels - follows HTM08
- Built-in record of calls
- Low battery and signal lost alert
- Operating Frequency: 433.92MHz
- Operating Range: 25m
- Power Supply: DC5V input, 2000mA

Standards:

EMC: Radio:	EN 55022EN
Alarm: Safety:	300220-1&2, EN
Medical Device	301489-1&3EN
Immunity:	50130-4EN 60950-
Manufacture:	1EN 60601-1-2 ISO
	9001:2008, ISO
	13485:2003

For more information, please contact:
Jimmy 012-8098169