PRODUCT

Eightfold Sdn Bhd (775128-W) 69-1, Jalan SS19/6, 47500 Subang Jaya, Selangor Darul Ehsan, Malaysia Tel: 03-5612 8169 Fax: 03-2726 8806 www.eightfold.com.my



X-RAY LED FILM VIEWER

Features

- High-efficient and durable LED light source technology
- High-definition film reading experience
- Innovative knob rotating and digital control technology
- Film sensing and constant current driving
- High frequency digital PWM technology
- Reliable silicon-rubber Film Clip Device
- Film sensor, constant current driver



	Ultra Slim Type	Ultra Slim Type
Pictures		
Model	EXV-SS	EXV-DS
View Panels	Single	Double
Illuminance	4000cd/m2 (adjustable between 0 – 4000 cd/m2)	
Color Temperature	8000K	
Brightness Uniformity	≥90	
LEDS Quantity	144pcs	144pcs*2
LEDS Lifespan (hours)	100,000 hours	
View Size(mm)	361*420	721*420
External Size (mm)	476*500*25	836*500*25
Input Voltage	AC90-240V, 50/60Hz	
Power	30W	60W
Application Condition	Room Average Illuminance ≤ 100 lux	
Application Scope	General film, digital Film, breast mammography film	
Brightness Adjustable Range	3 PWM dimming system brightness 0-100% stages continuous adjustable among 0 – 4000cd/m2	
Sensor function	Automatic sensing, memory function and delay power off	
Dimmer Switch	PWM Knob dimmer, easy to operate, precise and flexible	
LCD Display	3 digits display	

High Brightness type at 6000cd/m2 available. Please whatsapp to check.