

## CNC-3513-M – 4MP Motorized IP Dome



4 Mega

H.265+

30m IR

Motorized Zoom

Super Low Lux

Audio



POE

IP66

### Features

- **4 Megapixel** 1688x1520 @25fps
- **H.265+** Compression
- **2.8~12mm Motorized** Zoom Lens
- **Auto Focus**
- **Super Low Lux**
- DWDR, 3D-DNR, DSS, BLC, HLC, ROI, 3-stream etc
- LED Array, 0 Lux up to 30m
- Build-in Mic
- POE / 12VDC Dual Power
- Smart Functions : **Object Removal, Line Crossing, Region Intrusion**

### SPECIFICATION



Model	CNC-3513-M
Image Sensor	1/2.8" progressive scan CMOS Sensor
Resolution	1688x1520 @25fps (PAL)
Shuttle	1/25s ~ 1/100,000s
Lens	M14 2.8-12mm Motorized Zoom Auto Focus
Viewing Angle	72°~38°
LEDs	2nos 850nm IR LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Min. Illumination	0 Lux up to 30m (Subject to reflection)
Network	10/100-BaseT, RJ45
Bit Rate	64Kbps ~ 10Mbps
Compression	3-Stream : H.265 / H.264 / MJPEG
Working Environment	-20° ~ +50°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant/12VDC, Max. 6.5W
Dimension	111.5mm(φ) x 111.5mm(H), 0.65kg