



CNC-3813-MS-II – 8MP WDR SMART IP Dome



Features

- **8 Megapixel** @20fps
- **H.265+** Compression
- **2.8~12mm Motorized** Zoom Lens
- **Auto Focus, 120dB True WDR**
- 3D-DNR, DSS, BLC, HLC, Defog, ROI
- **Build-in Mic / Audio** In / Out
- **Alarm** In / Out
- POE / 12VDC Dual Power
- Support **μSD** up to 128GB
- Smart Functions : **Line Crossing, Area Intrusion, Item Care, Face Detection, People Counting, Human Detection, Population Density, Heat Map, Target Counting**

SPECIFICATION



141.00mm

Model	CNC-3813-MS-II
Image Sensor	1/2.8" progressive scan CMOS Sensor
Resolution	3840x2160 @20fps (PAL)
Shuttle	1/25s ~ 1/100,000s
Lens	M14 2.8-12mm Motorized Zoom Auto Focus
Viewing Angle	103°~32° Horizontal
LEDs	IR LED Array 30~50m Distance
Day & Night	Filter Change or TDN (True Day & Night)
Video Compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Audio Compression	G711A/U
Network	10/100-BaseT, RJ45
Bit Rate	64Kbps ~ 6Mbps
W. Environment	-30° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant/12VDC, Max. 10.5W
Dimension	141mm(φ) x 100.2mm(H), 0.89kg