



RP1104 - Remote Zone Control Panel

A remote zone controller with sensor touch buttons which allows the user to select input music source, volume and tones. It shall be installed at remote location at individual zone and connected to the MxP2288 controller via Cat5e / 6 UTP cable. Each controller shall run individually to each input port of the respective zone.

Power source	24V DC via MxP2288
Power consumption	100 mA
LCD panel	3.5" resistive touch screen
Communication	RS485 ; 19.2 Kbps
Controls	Volume / BGM source / tone controls
Cabling	Cat 5e / 6
Distance	Up to 500m
Dimensions (WxH)	86 x 86 mm
Color	White
Weight	100 g



PD1160 - 8/16 Zone Remote Paging Microphone

It is a simple and dedicated paging microphone for connection to MxP2288 MatriMix system with 8 / 16 zones call station.

- Multipoint paging with EX1102 mic extender
- Direct connection to MxP2288 controller.

Power requirement	24V DC via MxP2288 / TD6080
Power consumption	200 mA
Zone selection	8 / 16 zone keys with ALL CALL
Data connection	RJ45
Operating distance (data)	300 m
Audio distance	300 m
Indicators	Power, source, volume, busy
Dimensions (WxHxD)	150 x 186 x 62 mm (body only)
Weight	1.0 kg



EX1103 - Paging Mic Extender

When multipoint paging is required, EX1103 shall be used, with each PD1160 connected in series in a single circuit. The mic nearest to the Matrix controller shall have priority over its precedence.