



The Network Paging Console for the VEB Series is a state of the art touchscreen based paging console unit. It allows the user to operate the unit as well as select the zones via a user friendly GUI. From the GUI the operator will be able to make zone selection individually or in pre-defined groups based on the client's requirement. Being a network enabled console, the unit can be connected or relocated anywhere within the project without hassle - simply by connecting to the LAN's datapoint. Future upgrade to the unit will also allow the unit to communicate and make announcements via WIFI connection.



Technical Specifications

	VEB 43-10
Port Interface	Rj45 10/100 Mbps Ethernet TCP/IP Connectivity Stereo/Mono (Stream)
Graphic Display	10 inch touch screen, resolution 1920 x 1080 pixels
Microphone	Non-removable gooseneck condenser capsule Unidirectional microphone with windshield
Chime	2 Tone Ascending and 2 Tone Descending. (User customizable)
Power Supply	12 Vdc, 2.5 A
Power Consumption	18W
Audio Input	Condenser, 1 Vrms, unbalanced
Audio Output	VectusNET PCM Uncompressed Audio
Monitor Speaker	8Ω 1W 1" speaker
Frequency Response	20Hz – 18kHz
Signal to Noise Ratio	>90dB @ 1KHz
Network I/F	10BASE-T/100BASE-T
Network Protocol	VectusNET
Operation Temperature	0°C – 40°C
Operation Humidity	Less than 90% Relative Humidity
Dimensions	195 x 65 x 190 mm (Mic only)
Accessories	Power Adapter (DC 12V/2.5A) Microphone Windscreen Metal Standing Bracket