

Silver Black

Elegant MINIMALISTIC

Mini compact size access reader



Inspired , Stylish, Redefined...

Minimalistic design allow it to look simple but elegant. Easily blend into any interior design.


Dark SilverBlack color concept further enchance modern contemporary impression of your office. Compact mini size allow it to easily fit into narrow door frame with limited space.







Dimension AR723HN/AR721U



SE-ACS software is available in 3 versions as follows:



Single PC, Single RS485 or TCPIP connection, simple time attendance



SOYALetegr

Multiple PC within LAN, Multiple RS485 or TCPIP connection, CCTV picture capture up to 8 camera, advance time attendance



Multiple PC within LAN and internet (multi branch), Multiple RS485 or TCPIP connection, CCTV picture capture unlimited camera, advance time attendance, Emap

Clean and intuitive GUI help you search for access activity super fast



Flexible time attendance to automate clocking report and monitor staff punctuality



Advance version support multiple overnight shift and flexible shift. Attendance will calculate work time, over time, late arrive and early go back.

E-Map pin point threat location and helps you response to alarm faster



E-map will automatically pop up according to alarm

Model AR723HN AR723HN_M Frequency 125KHz 13.56MHz Standard EM Standard Mifare ISO14443A

2-8cm

5-12cm

RS-485

1.024

1,200

9600 bps(N,8,1)

-20°C to +60°C

ON/OFF, 0.1-600 Sec.

Toggle, 1-600 Sec. Limit Switch (Form C)

1 Wiegand Port

Yes (M4/M8 Only)

Yes (M4/M8 Only)

Alarm / Duress

IP56 (Optional)

ABS

Black

32 Floors, 1,024 Users

1 Bi-Color LED & 1 Beeper No(Option:AR-WG-KEYBOARD-M

Standalone/ Networking

Arming LED (or Security trigger signal) /

11/63(Connect to Multi-Door Networking Controller)

60±5

External Relay

Egress(R.T.E.) / Door contact

Reading Range (Depends on Tags) Power Supply

lower Supply 19-16VDC ver consumption <1W

Communication Interface

Baud Rate
Temperature
Digital Input

Relay Output Lock Relay Time

Alarm Time
Tamper Switch
User Capacity

External Reader
Anti-pass-back
Lift Control

Serial port LCD Panel

Ingress Protection


Keypad Material
Housing Material
Time Zone
Operation Mode

Color

Dimensions (mm)
Weight (g)


81(L)X43(W)X18(H) 40±5 | ::•

RS485 network connection



Multi door, 15,000 card users, global anti-passback

TCPIP network connection



Standalone connection

