



Technical Information

Vanatur Classic

*Vanatur is licensed to produce Patented 'Locking system' by Valinge Aluminum AB, Sweden.

Characteristic	Standard	Requirement	Specification
Thickness	-	-	8mm
Dimension	-	-	192 x 1205mm
Core Material	-	-	High Moisture Resistance HDF
Surface Texture	-	-	Original Woodgrain
Thickness swelling	EN 13329	< 18%	< 8%
Formaldehyde emission	EN 717-1	-	E1
Level of use	EN 13329	Class 23/31	Class 23/31
Abrasion resistance	EN 13329	AC3	AC3
Impact resistance	EN 13329	IC1	IC1
Fire Resistance	BS 476 Part 7	-	Class 2
Surface stain resistance	EN 13329	5, (group 1&2) 4, (group 3)	5, (group 1, 2 & 3) (No visible change)
Resistance to cigarette burns	EN 13329	Rating 4	Rating 4
Light fastness	EN 13329	> 6	Better than 6 (Blue wool scale)
Effect of a furniture leg	EN 13329	-	No damage shall be visible When tested with foot type 0
Effect of a castor chair	EN 13329	-	No change in appearance or damage
Surface Soundness	EN 13329	> 1.0 N/ sq mm	> 1.0 N/ sq mm