

FLOOR CULTURE HOLDINGS SDN BHD (1060537-W)
NO. 8, JALAN TS 6/9,
TAMAN PERINDUSTRIAN SUBANG,
47500 SUBANG,
SELANGOR
TEL: 03-5636 2922 FAX: 03-8081 2923
WEBSITE: www.floorculture.com

PRODUCT SPECIFICATION OF BKB HEVEA PRODUCTS
PRODUCT: 3 – PLY ENGINEERED WOOD FLOORING
SPECIFICATION: FULL PLANK, 2 STRIP, 3 STRIP AND FINELINE

| Construction: | |
|--|--|
| Type | 3 Layer Engineered Flooring |
| Surface layer composition | 1 strip and Fineline 1 lamella |
| | 2 strip 2 + 2; 2+3 and 3+3 |
| | 3 strip Random pattern |
| Profile | Tongue and Groove, 5G LOC |
| Moisture content | 7% ± 1% |
| Dimensions: | |
| Thickness – BKB Parquet | 14.0mm ± 0.5mm |
| Thickness of top layer | 3.5mm ± 0.5mm |
| Thickness of middle layer (core strip) | 8.8mm ± 0.2mm |
| Thickness of bottom layer (veneer) | 2.0mm ± 0.1mm |
| Surface layer length (panel) | 2190mm +0/-20mm 1830 mm +0/-20mm (shortfall is compensated by under-declaration of content/pack) |
| Surface layer width (panel) | (190mm/180mm/ 138mm/ 125mm) +/- 0.1mm |
| Height difference between panels | 0.2 mm (max.) |
| Finishing and Adhesive: | |
| Varnish | Treated with water based Primer + 6 coats of UV Acrylic |
| Oil | Industrial natural oil /UV oil |
| Gloss level of surface layer | Low gloss : 7 ± 3% |
| | Normal gloss : 25 ± 5% |
| | High gloss : 50 ± 5% |
| Glue | Urea Formaldehyde – E1 class EPI – conforms to F***** standard |
| Packing | |
| Packaging | BKB/ White |
| Weight per pack | ~20kg (6 pieces/ pack) |
| Nested layers | Full plank Minimum 4 layers full length, remainder nested. |
| | 2 strip, 3 strip and Fineline Minimum 5 layers full length, remainder nested. |
| | Full plank – Cherry and Walnut Minimum 3 layers full length, remainder nested. |

FLOOR CULTURE HOLDINGS SDN BHD (1060537-W)
NO. 8, JALAN TS 6/9,
TAMAN PERINDUSTRIAN SUBANG,
47500 SUBANG,
SELANGOR
TEL: 03-5636 2922 FAX: 03-8081 2923
WEBSITE: www.floorculture.com

PRODUCT SPECIFICATION OF BKB HEVEA PRODUCTS

PRODUCT: 3 – PLY ENGINEERED WOOD FLOORING

SPECIFICATION: FULL PLANK, 2 STRIP, 3 STRIP AND FINELINE

| Properties: | Declaration according to EN 13432 |
|---|--|
| 1. Fire resistance according to EN 13501-1 | D _{fl} S1 classified according to EN 1350-1 |
| 2. Formaldehyde emission according to EN 717-1 | Class E1 |
| 3. Anti skid properties according to EN 1339 | USRV 15 and USRV 20 |
| Opening between panels (when laid) | According to DIN EN13489 |
| Recognized certification | MS ISO 9001 – 2008, FSC, PEFC, Singapore Green Label, National technical approval Z-156.607-1066, CE, F4 Star Ministerial Approval |
| Recommended maintenance | As per BKB's Maintenance programme |
| Warranty | As per BKB's Standard Limited Warranty |
| Sub floor and installation requirements: | |
| Installation | Above and below grade |
| Level | Not exceed 4mm per 2000mm length |
| Moisture content | Moisture content not to exceed 4.5% |
| Moisture barrier | Recommended 0.2mm polyethylene with 200mm overlap and sealed with adhesive tape. |
| Underlay (Free float installation) | Recommended 3mm thick underlay made of cork, corrugated cardboard, rubber, or similar to cover any minor unevenness and as sound deadening. |
| Glue down installation | BKB Engineered Flooring can be glued down to concrete, plywood or chipboard subfloor. Glue to be applied to both side of the underlay. Glue used must have minimum solid content of 76%. |