

# Excellent colour quality communication

The imageRUNNER ADVANCE C7500i III series delivers excellent productivity and colour quality for your business. Targeted for high print volume environments, the series has versatile finishing options, making it an ideal investment for both internal and client facing communications. It also provides an intuitive experience for the user and safeguards information, making this series a valuable addition to your business.



## WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Professional finishing options including staple, saddle stitch, punch, trim, fold and insert for versatile document creation in house.

## COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Seamless integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

## SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- Ensure device is safe from unknown firmware installation with system verification at startup.
- Integrate with third-party solutions for complete monitoring protection.

## QUALITY AND RELIABILITY

- V<sup>2</sup> Colour technology maximises the capability of the device and toner to deliver impressive results with a vivid and vibrant appearance.
- VCSEL (Vertical Cavity Surface Emitting Laser) technology, more commonly found in production machines is adopted with a 2,400dpi laser resolution while maintaining productivity.
- Canon's consistently vivid (CV) toner helps achieve stunning colour consistency and accuracy across a wide variety of media, even in print intensive environments.
- Canon's signature reliability and engine technologies provide high quality output to meet the needs of modern workplaces.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and optional Adobe® PostScript® 3™ print driver allows seamless integration with enterprise applications.

- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

## SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimising environmental impact.
- Consumes as little as 0.9W in sleep mode.

## CONFIGURATION

**STAPLE FINISHER-V2**

- 3 tray, 3,500 sheets capacity
- Corner and double stapling up to 65 sheets (52-90gsm)
- Supports ECO-staple 4 sheets (65-81gsm) and Staple-on-Demand 65 sheets (52-90gsm)
- Supports optional Internal 2/4 and 2/3 hole punchers (2/F4 Hole Puncher Unit-A1 and 2/3 Hole Puncher Unit-A1)

**BOOKLET FINISHER-V2**

- 3 tray, 3,500 sheets capacity
- Corner and double stapling up to 65 sheets (52-90gsm)
- Supports ECO-staple 4 sheets (65-81gsm) and Staple-on-Demand 65 sheets (52-90gsm)
- Supports optional Internal 2/4 and 2/3 hole punchers (2/F4 Hole Puncher Unit-A1 and 2/3 Hole Puncher Unit-A1)

**STAPLE FINISHER-X1**

- 3 tray, 4,250 sheets capacity
- Corner and double stapling up to 100 sheets (52-80gsm)
- Supports optional Internal 2/4 and 2/3 hole punchers (Puncher Unit-BG1 (2/F4H) and Puncher Unit-BF1(2/3H))

**BOOKLET FINISHER-X1**

- 3 tray, 4,250 sheets capacity
- Corner and double stapling up to 100 sheets (52-80gsm)
- Booklet-making up to 20 sheets
- Supports optional Internal 2/4 and 2/3 hole punchers (Puncher Unit-BG1 (2/F4H) and Puncher Unit-BF1(2/3H))

**DOCUMENT INSERTION UNIT-G1**

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheets capacity

**DOCUMENT INSERTION/FOLDING UNIT-K1**

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheets capacity
- Z-fold and C-fold

**DOCUMENT INSERTION UNIT-N1**

- Insert pre-printed sheets
- Up to A3
- 2-tray, 400 sheets capacity

**PAPER FOLDING UNIT-J1**

- Insert pre-printed sheets
- Up to A3
- Z-fold, Accordion Z-fold, C-fold, Half-fold and Double Parallel fold

**MULTI FUNCTION PROFESSIONAL PUNCHER-A1**

- Up to A3
- Media Weight 52 - 300 gsm

**UPRIGHT CONTROL PANEL-H1**

**COPY TRAY-R2**

**BUFFER PASS UNIT-M1**

**PAPER DECK UNIT-E1**

- Supports A4
- Media weight 52 - 256 gsm
- 3,500 sheets (80gsm)

**POD DECK LITE-C1**

- Supports up to A3
- Media weight 52 - 300 gsm
- 3,500 sheets (80gsm)

**MULTI DRAWER PAPER DECK-C1**

- Supports up to A3
- Media weight 52 - 300 gsm
- 6,000 sheets (80gsm)

**imagePASS-N2**

PDL · PCL/PS  
 MEMORY · 2GB/500GB  
 SYSTEM · Fiery FS200

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules

# Main Unit

Type  
A3 Colour Laser Multifunctional

Core Function  
Print, Copy, Scan, Send, Store and Optional Fax

Processor  
Canon Dual Custom Processor (Shared)

Control Panel  
Standard: 10.1 inch TFT LCD WSVGA Colour Touch Panel  
10.4 inch TFT LCD WSVGA Colour Upright Touch Panel

Memory  
Standard : 4.0GB RAM

Hard Disk Drive  
Standard : 250GB  
Maximum : 1TB

Mirroring Hard Disk Drive  
Optional 250GB, 1TB

Interface Connection  
**Network** Standard : 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)  
Optional : NFC, Bluetooth Low Energy  
**Others** Standard : USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)  
Optional : Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)  
Standard: 3,550 sheets (2 x 1,100-sheet Paper Cassette, 2 x  
550-sheet Paper Cassette, 250-sheet Multi-purpose tray)  
Maximum: 9,300 sheets (with Multi-Drawer Paper Deck-C1)

Paper Output Capacity (A4, 80gsm)  
Standard : 250 Sheets (with COPY TRAY-R2)  
Maximum : 4,250 Sheets  
(with STAPLE FINISHER-X1 or BOOKLET  
FINISHER-X1)

Finishing Capabilities  
Standard : Collate, Group  
With External Finisher:  
Collate, Group, Offset, Staple, Saddle Stitch<sup>1)</sup>, Hole Punch<sup>2)</sup>  
(multiple patterns), ECO-Staple<sup>3)</sup>, Staple-on-Demand<sup>3)</sup>,  
Document Insertion<sup>4)</sup>, Fold (C-/Z-/Half\*/Double parallel\*/  
Accordion-Z fold\*), Trimming<sup>7)</sup>

\*1 Requires Booklet Finisher-V2 or Booklet Finisher-X1  
\*2 Requires 2/3 Hole Puncher Unit-A1 or 2/4 Hole Puncher Unit-A1  
(with Staple Finisher-V2 or Booklet Finisher-V2), Puncher Unit-BF1 or  
Puncher Unit-BG1 or Multi Function Professional Puncher-A1/B1 (with  
Staple Finisher-X1 or Booklet Finisher-X1)  
\*3 Requires Staple Finisher-V2 or Booklet Finisher-V2  
\*4 Requires Document Insertion Unit-G1 or Document Insertion/Folding  
Unit-K1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Document  
Insertion Unit-N1 (with Staple Finisher-X1 or Booklet Finisher-X1)  
\*5 Requires Document Insertion/Folding Unit-K1 (with Staple Finisher-V2  
or Booklet Finisher-V2) or Paper Folding Unit-J1 (with Staple  
Finisher-X1 or Booklet Finisher-X1)  
\*6 Requires Paper Folding Unit-J1 (with Staple Finisher-X1 or Booklet  
Finisher-X1)  
\*7 Requires Inner Booklet Trimmer-A1 (with Booklet Finisher-X1)

Supported Media Types  
**PAPER CASSETTES (1/2):**  
Thin, Plain, Recycled, Thick, Colour, Transparency, Pre-  
punched, Letterhead, Bond

**PAPER CASSETTES (3/4):**  
Thin, Plain, Recycled, Thick, Colour, Tab, Transparency, Bond,  
Pre-punched, Letterhead, Envelope

**MULTI-PURPOSE TRAY:**  
Thin, Plain, Recycled, Thick, Colour, Transparency, Label,  
Tracing, Envelope, Coated, Textured, Bond, Pre-punched,  
Letterhead, Tab

Supported Media Sizes  
**PAPER CASSETTES (1/2):**  
Standard size : A4, B5  
**PAPER CASSETTES (3/4):**  
Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, SRA3  
Envelope [No.10 (COM10), Monarch, DL, ISOC5]  
Envelope custom size: 98.0 x 148.0 mm to 330.2 x 487.7 mm  
Custom Size : 139.7 mm x 182 mm to 330.2 mm x 487.7 mm

**MULTI-PURPOSE TRAY:**  
Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,  
Envelope [No.10 (COM10), Monarch, ISO-C5, DL]  
Envelope custom size: 90.0 x 148.0 mm to 330.2 x 487.7 mm  
Custom size : 100.0 x 148.0 mm to 330.2 x 487.7 mm  
Free size : 100.0 x 182.0 mm to 330.2 x 487.7 mm

Supported Media Weights  
Paper Cassettes (1/2) : 52 to 220 gsm  
Paper Cassettes (3/4) : 52 to 256 gsm  
Multi-purpose tray : 52 to 300 gsm  
Duplex : 52 to 220 gsm

Warm-up Time  
From Power On : 30 Seconds or Less<sup>1)</sup>  
From Deep Sleep Mode : 30 Seconds or Less  
Quick Startup Mode : 4 seconds<sup>2)</sup>

\*1 Time from device power-on, until copy ready  
\*2 Time from device power-on to when key operations can be  
performed the touch panel display.

Dimensions (W x D x H) 689 mm x 941 mm x 1,220 mm

Installation Space (W x D)  
1,758mm x 1,524mm (with Front door open + Multi-purpose  
tray/upper-right cover open + Left cover open)

2,026mm x 1,524 mm (with Front door open + Multi-purpose  
tray/upper-right cover open + Buffer Pass-M1 + Booklet  
Finisher-V2/extension tray & rotary tray extended)

Fully Configured: 3,818mm x 1,524 mm (with Multi-Drawer  
Paper Deck-C1 + Buffer Pass-M1 + Document Insertion  
Unit-N1 + Multi Function Professional Puncher-A1 + Paper  
Folding Unit-J1 + Booklet Finisher-X1)

Weight Approx. 271kg (including ADF and toner)

## Print Specifications

Print Speed (Simplex, BW/Colour)  
iR-ADV C7580i III Up to (ppm): 80/70 ppm (A4, A5, A5R, A6R)  
40/35 ppm (A3)  
iR-ADV C7570i III Up to (ppm): 70/65 ppm (A4, A5, A5R, A6R)  
35/32 ppm (A3)

Print Resolution (dpi)  
Data Processing Resolution:  
600 x 600 (Default), 1,200 x 1,200 (Up to)  
Output Resolution: 2,400 x 2,400

Page Description Languages  
Standard: UFR II, PCL6  
Option: Adobe Postscript 3

Direct Print  
Direct printing available from USB memory, Advanced box,  
Remote UI and Web Access\*  
Supported File Types: PDF, TIFF, JPEG, EPS, XPS  
\*Only PDF print from websites is supported.

Printing from mobile and cloud  
AirPrint, Mopria, Google Cloud Print, and Canon Print  
Business, and uniFLOW Online

Fonts  
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T<sup>1)</sup> (Japanese, Korean,  
Simplified and Traditional Chinese), Barcode  
fonts<sup>2)</sup>  
PS fonts: 136 Roman

\*1 Requires optional PCL INTERNATIONAL FONT SET-A1  
\*2 Requires optional BARCODE PRINTING KIT-D1

Operating System  
UFR II: Windows 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016, MAC OS X  
(10.7 or later)

PCL: Windows 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016

PS: Windows 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016, MAC OS X  
(10.7 or later)

PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

## Copy Specifications

Copy Speed (BW/Colour)  
iR-ADV C7580i III Up to (ppm): 80/70 ppm (A4, A5, A5R, A6R)  
40/35 ppm (A3)  
iR-ADV C7570i III Up to (ppm): 70/65 ppm (A4, A5, A5R, A6R)  
35/32 ppm (A3)

First-Copy-Out Time (A4, BW/CL)  
iR-ADV C7580i III: Approx. 4.4/5.4 seconds or less  
iR-ADV C7570i III: Approx. 4.8/5.9 seconds or less

Copy Resolution (dpi)  
Reading : 600 x 600  
Printing : up to 2,400 x 2,400

Multiple Copies  
Up to 9,999 copies

Copy Density  
Automatic or Manual (9 Levels)

Magnification  
25% - 400% (1% Increments)

Preset Reductions  
25%, 50%, 61%, 70%, 81%, 86%

Preset Enlargements  
115%, 122%, 141%, 200%, 400%

## Scan Specifications

Type  
Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity (80 gsm)  
300 Sheets

Acceptable Originals and Weights  
Platen: Sheet, Book, 3-Dimensional Objects  
(Height: Up to 50 mm, Weight: up to 2kg)

Document Feeder media weight: (BW/CL)  
1-sided scanning: 38 to 220 gsm/64 to 220 gsm  
2-sided scanning: 50 to 220 gsm/64 to 220 gsm

Supported Media Sizes  
Platen: max. scanning size: 297 x 431.8mm  
Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5,  
B5R, B6R  
Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm

Scan Speed (A4, BW/CL)  
1-sided Scanning (ipm) : 120/120 (300dpi),  
120/70 (600 dpi)  
2-sided Scanning (ipm) : 240/220 (300dpi),  
150/90 (600 dpi)

Scan Resolution (dpi)  
600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

Pull Scan Specifications  
Color Network ScanGear2. For both Twain and WIA  
Supported OS: Windows 7/8.1/10/Server 2008/Server 2008  
R2/Server 2012/Server 2012 R2/Server 2016

## Send Specifications

Destination  
E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail  
Box, Super G3 FAX (Optional), IP Fax (Optional)

Address Book  
LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution (dpi)  
600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

Communication Protocol  
File : FTP (TCP/IP), SMB v3.0, WebDAV  
E-mail/I-Fax : SMTP, POP3

File Format  
Standard : TIFF, JPEG, PDF (Limited Color, Compact,  
Apply policy, Optimize for Web, PDF A/1-b,  
Encrypted, Device Signature), XPS (Compact,  
Device Signature),  
Optional : PDF (Trace & Smooth, Searchable, User  
Signature), XPS (Searchable, User Signature),  
Office Open XML (PowerPoint, Word)

## Fax Specifications

Optional/Standard Optional on all models

Maximum Number of Connection Lines 4

Modem Speed  
Super G3 : 33.6 kbps  
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200,  
200 x 100

Sending/Recording Size A3, A4, A4R, A5<sup>1)</sup>, A5R<sup>1)</sup>, B4,  
B5<sup>2)</sup>, B5R<sup>1)</sup>  
<sup>1)</sup> Sent as A4 <sup>2)</sup> Sent as B4

FAX Memory Up to 30,000 pages

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

## Store Specifications

Mail Box (Number supported)  
100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
30,000 Maximum Pages Stored

Advanced Box  
Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows (Windows 7/8.1/10)  
Concurrent Connections (Max.): SMB: 64, WebDAV:  
3 (Active Sessions)

Advanced Box Available Disc Space  
Approx. 16GB (Standard HDD)  
Approx. 480GB (with option 1TB HDD)

Memory Media  
Standard: USB Memory

## Security Specifications

Authentication  
Standard : User Authentication (Picture Login/Keyboard  
Authentication), DepartmentID Authentication,  
Access Management System

Optional: My Print Anywhere secure print (Requires  
uniFLOW), uniFLOW Online Express Cloud  
based management software

Data  
Standard: Trusted Platform Module (TPM), Hard Disk  
Password Lock, Hard Disk Drive Erase,  
Mail Box Password Protection, Hard Disk Drive  
Encryption (FIPS140-2 Validated)

Optional : Hard Disk Drive Mirroring, Hard Disk Drive  
removal, IEEE 2600.2 Common Criteria  
Certification, Data Loss Prevention (Requires  
uniFLOW/iWSAM Express)

Network  
Standard : IP/Mac Address Filtering, IPSEC, TLS Encrypted  
Communication, SNMP V3.0, IEEE802.1X,  
IPv6, SMTP Authentication, POP Authentication  
before SMTP, S/MIME

## Document

Standard : Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks

Optional : User signature, Document Scan Lock

## Environmental Specifications

### Operating Environment

Temperature: 10 to 30 °C  
Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

iR-ADV C7580i III : 220-240 V (±10 %), 50/60 Hz (±2 Hz), 11 Amp  
iR-ADV C7570i III : 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp

### Power Consumption

Maximum iR-ADV C7580i III : 2,500 W  
iR-ADV C7570i III : 2,000 W  
Standby : Approx. 136.6 W<sup>\*1</sup>  
Sleep mode : Approx. 0.9 W<sup>\*2</sup>

\*1 Reference Value: measured one unit

\*2 0.9W sleep mode is not available in all circumstances due to certain settings.

## Consumables

Toner NPG-72 TONER BK/C/M/Y

Toner Yield (Estimated Yield @5% Coverage)

NPG-72 Toner BK : 82,000 pages  
NPG-72 Toner C/M/Y : 66,500 pages

## Software and Printer Management

### Tracking and Reporting

Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device.

uniFLOW Online Express: Combining with ULM you can gain further control, highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.

### Remote management tools

iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring of consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management).

eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance).

Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.

### Scanning software

Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.

### Optimisation Tools

Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers

NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.

### Platform

MEAP (Multifunction Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device.

MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services

## Paper Supply Options

### PAPER DECK UNIT-E1

Paper Capacity : 3,500 sheets (80 gsm)  
Paper Types : Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond  
Paper Size : A4, B5  
Paper Weight : 52 to 256 gsm  
Power Source : From the Main Unit  
Dimensions (W x D x H) : 340mm x 630mm x 572 mm (attached to the main unit)  
Weight : Approx. 34.0 kg

### POD DECK LITE-C1

Paper Capacity : 3,500 sheets (80 gsm)  
Paper Type : Thin, Plain, Recycled, Colour, Thick, Pre-punched, Label, Letterhead, Bond, Coated, Transparency, Tab, Tracing, Envelope\*, Textured  
Paper Size : A3, A4, A4R, A5R, B4, B5, B5R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5] Custom size: 139.7mm x 148.0 mm to 330.2mm to 487.7mm  
Paper Weight : 52 to 300 gsm  
Power Source : 220-240V/1.2A 50/60Hz  
Dimensions (W x D x H) : 633mm x 686mm x 574 mm (attached to the main unit)  
Weight : Approx. 68.0 kg

\*Requires Envelope Feeder Attachment-G1

### MULTI-DRAWER PAPER DECK-C1

Paper Capacity : 6,000 sheets (2,000 sheets x 3 drawers, 80 gsm)  
Paper Type : Thin, Plain, Recycled, Colour, Thick, Pre-punched, Label, Letterhead, Bond, Coated, Transparency, Tab, Textured  
Paper Size : A3, A4, A4R, A5R, B4, B5, B5R  
Custom size : 139.7 mm x 182.0 mm to 330.2 mm x 487.7mm  
Paper Weight : 52 to 300 gsm  
Power Source : 220-240V/1.7A 50/60Hz  
Dimensions (W x D x H) : 950 mm x 797 mm x 1,040 mm  
Weight : Approx. 155.0 kg

## Hardware Accessories

### Card Readers

COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-A4

### Others

TAB FEEDING ATTACHMENT-F1  
UTILITY TRAY-B1

## Security Options

Document Security  
DOCUMENT SCAN LOCK KIT-B2

### Data Security

HDD MIRRORING KIT-J1  
2.5 INCH/250GB HDD-N1  
2.5 INCH/1TB HDD-P1  
REMOVABLE HDD KIT-AL1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1  
PCL ASIAN FONT SET-A1  
PS PRINTER KIT-BF1  
PS PRINTER KIT-BW1

### Send Accessories

UNIVERSAL SEND ADVANCED FEATURE SET-H1 (TRACE & SMOOTH PDF, SEARCHABLEPDF/XPS, OFFICE OPEN XML)  
UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1

### Barcode Printing

BARCODE PRINTING KIT-D1

### EFI-Fiery Based Controller (Embedded)

IMAGEPASS N2

### EFI-Fiery Based Controller Options

FIERY IMPOSE  
FIERY COMPOSE  
FIERY IMPOSE AND COMPOSE

### System Accessories

SERIAL INTERFACE KIT-K3  
BLE CONNECTION KIT-A1  
NFC KIT-A1 (FOR UPRIGHT CONTROL PANEL)  
NFC KIT-C1

### Fax Accessories

SUPER G3 FAX BOARD-AS1  
SUPER G3 2ND LINE FAX BOARD-AS1  
SUPER G3 3RD/4TH LINE FAX BOARD-AS1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1

### Consumables

STAPLE-N1  
STAPLE-P1  
STAPLE CARTRIDGE-X1  
STAPLE CARTRIDGE-Y1

To arrange for a demonstration, simply contact any of our offices below.

### SOUTH & SOUTHEAST ASIA

#### REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #15-01 Galaxis Singapore 138522

Tel: 65-6799 8888 | Fax: 65-799-8882 | www.canon-asia.com | www.canon.com.sg



Partner/Dealer Stamp



This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated

0216W118 © 2019 Canon Singapore Pte. Ltd.  
All rights reserved. Printed in Singapore.