

JW-E Series Economic Vertical Packing Machine



Feature:

- PLC control, man_machine Interface, easy to operate and maintenance.
- Driven by servo motor and optical tracking devices to keep accuracy.
- The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application:

- Applicable bag type: Pillow bag, Gusset Bag, Seal type bag.
- Applicable film materials: A variety of laminated films, single-layer PE film, Film thickness range 0.04mm~0.15mm.
- Applicable packing materials: A variety of recreation food, frozen food, coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.

Specifications

Model	JW-E3220	JW-E4230	JW-E5235	JW-E6240	JW-E7245
Film width	140~320mm	160~420mm	180~520mm	180~620mm	200~720mm
Bag size	L*W=(60~200)mm*(50~150)mm	L*W=(60~300)mm*(60~200)mm	L*W=(60~350)mm*(70~250)mm	L*W=(70~400)mm*(80~300)mm	L*W=(70~450)mm*(80~350)mm
Packing speed	15~70 bags / min	15~65 bags / min	15~60 bags / min	15~50 bags / min	0~70 bags / min
Power requirement	2.15 KW / 220V / 50 (60) HZ	3.4KW / 220V / 50 (60) HZ	3.4 KW / 220V / 50 (60) HZ	3.6 KW / 220V / 50 (60) HZ	5.5 KW / 220V / 50(60) HZ
Gas pression	0.6Mbra	0.6Mbra	0.6Mbra	0.6Mbra	0.6MPa
Gas consumption	0.5m ³ /min	0.6m ³ /min	0.7m ³ /min	0.8m ³ /min	0.4m ³ /min
Machine size	L*W*H=1158mm*930mm*1213mm	L*W*H=1465mm*1040mm*1470mm	L*W*H=1540mm*1160mm*1600mm	L*W*H=1640mm*1226mm*1709mm	L*W*H=1748mm*1344mm*1955mm
Machine weight	350Kg	400Kg	450Kg	550Kg	630Kg

JW-H Series Double Servo Motor Vertical Packing Machine



Feature:

- PLC control, man-machine interface, easy to operate and maintenance.
- Driven by double servo motor and optical tracking devices to keep high packing speed and high accuracy.
- The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application:

- Applicable bag type: Pillow bag, Gusset bag, Seal type bag.
- Applicable film materials: A variety of laminated films, single-layer PE film, Film thickness range 0.04mm~0.15mm.
- Applicable packing materials: A variety of recreation food, frozen frozen food , coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.

Specifications

Model	JW-H3220	JW-H4230	JW-H5235	JW-H6240	JW-H7245
Film width	140~320mm	160~420mm	180~520mm	180~620mm	200~720mm
Bag size	L*W=(60~200)mm*(50~150)mm	L*W=(60~300)mm*(60~200)mm	L*W=(60~350)mm*(70~250)mm	L*W=(70~400)mm*(80~300)mm	L*W=(70~450)mm*(80~350)mm
Packing speed	15~100bags/min	15~100bags/min	15~90bags/min	15~85bags/min	15~70 bags / min
Power requirement	2.9 KW/220V/50(60)HZ	4.5KW/220V/50(60)HZ	4.5KW/220V/50(60)HZ	5.1KW/220V/50(60)HZ	5.5 KW / 220V / 50(60) HZ
Gas pression	0.6MPa	0.6MPa	0.6MPa	0.6MPa	0.6MPa
Gas consumption	0.15m ³ /min	0.2m ³ /min	0.2m ³ /min	0.2m ³ /min	0.4m ³ /min
Machine size	L*W*H=1158mm*930mm*1213mm	L*W*H=1400mm*1100mm*1560mm	L*W*H=1514mm*1154mm*1590mm	L*W*H=1640mm*1226mm*1709mm	L*W*H=1748mm*1344mm*1955mm
Machine weight	350Kg	500Kg	550Kg	600Kg	680Kg

JW-M Series Vertical Packing Machine



Feature:

- PLC control, man-machine interface, easy to operate and maintenance.
- Driven by servo motor and optical tracking devices to keep accuracy.
- The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application:

- Applicable bag type: Pillow bag, Gusset Bag. Seal type bag.
- Applicable film materials: A variety of laminated films, single-layer PE film, Film thickness range 0.04mm~0.15mm.
- Applicable packing materials: A variety of recreation food, frozen food, coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.

All packing machines Optional devices:

- Gusset device
- Punching device
- Exhaust / inflatable devices
- PE film sealing
- Anti-Static electricity
- Horizontal seal cooling
- Nitrogen Charging device
- Vibrating device
- Sealing device
- Easy tear device
- Bag support device
- Evacuating device
- Film rectify deviation adjust device
- Horizontal sealing servo motor

Common related equipment:

- Multihead weigher / linear weigher
- Cup Measuring machine
- Auger Filler
- Liquid Pump

Specifications

Model	JW-M4230	JW-M5235
Film width	160~420mm	180~520mm
Bag size	L*W=(60~300)mm*(60~200)mm	L*W=(60~350)mm*(70~250)mm
Packing speed	15~60bags/min	15~60bags/min
Power requirement	3.4KW/220V/50(60)HZ	3.4 KW/220V/50(60)HZ
Gas pression	0.6Mbra	0.6Mbra
Gas consumption	0.6m ³ /min	0.6m ³ /min
Machine size	L*W*H=1400mm*1100mm*1560mm	L*W*H=1514mm*1154mm*1620mm
Machine weight	480Kg	520Kg