

Products & Parameters for packing machine

NO.	Product Model	Product Photo	Brief Introduction	Photo
1	Simple electric lower half		<p>Working Power:600W Appearance Size: 65*50*132cm Weight: 50kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤130mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≧70 L Configuration: 4.3"touch screen,three-sided seal or back seal Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine, and other filling machines.</p>	
2	Simple pneumatic lower part		<p>Working Power:600W Appearance Size: 77*50*131cm Weight: 50kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤130mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≧70 L Configuration: 4.3"touch screen,three-sided seal or back seal Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine, and other filling machines.</p>	

3	Shanshui Type lower half (LQ6)		<p>Working Power:600W Appearance Size: 88*50*133cm Weight: 65kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤130mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≧70 L Configuration: 4.3"touch screen,three-sided seal or back seal Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine, and other filling machines.</p>	
4	Lower half (right electric control box)		<p>Working Power:650W Appearance Size: 89*60*165cm Weight: 75kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤150mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≧70 L Configuration: 4.3"touch screen,three-sided seal or back seal, independent electric cabinet,independent temperature control. Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine, and other filling machines.</p>	

5	Lower half(right electric control box and acrylic)		<p>Working Power:650W Appearance Size: 83*60*163cm Packing Size: 93*64*111cm Net weight: 80kg Gross weight: 105kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤150mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≥70 L Configuration: 4.3"touch screen,three-sided seal or back seal, independent electric cabinet,independent temperature control,transverse sealing mechanism coated with teflon anti-stick copper,ave acrylic protective cover. Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine, and other filling machines.</p>	
6	Lower half (PLC320)		<p>Working Power:680W Appearance Size: 92*68.5*175cm Weight: 90kg Packing Speed: 1200-1500 (pcs/h) Max width of bag: ≤150mm Power Requirements: Need air compressor Air compressor displacement: 0.36m³/min Air storage of air compressor: ≥70 L Configuration: 7"touch screen,three-sided seal or back seal, independent electric cabinet,independent temperature control,transverse sealing mechanism coated with teflon anti-stick copper,ave acrylic protective cover. Application: It can be matched with sauce filling machine (3-30/5-50/10-100/25-125/50-250/50-500ml) , 100g double heads filling machine, 600g double heads filling machine,600g four heads filling machine,1500g double heads filling machine, 1500g four heads filling machine, and other filling machines.</p>	

7

Lower half (PLC420)



Working Power:680W
Appearance Size: 106*79*199cm
Weight: 120kg
Packing Speed: 1200-1500 (pcs/h)
Max width of bag: ≤200mm
Power Requirements: Need air compressor
Configuration: Acrylic protective cover, 7"touch screen,three-sided seal or back seal,industrial grade PLC control system, independent electric cabinet, independent temperature control,transverse sealing mechanism coated with teflon anti-stick copper,clip-pulling film mechanism
Application: It can be matched with sauce filling machine (200-1000/200-2000ml) , 100g four heads filling machine, 600g four heads filling machine,1500g double heads filling machine, 1500g four heads filling machine, and other filling machines.

