

CONNECTABLE POLES

INSULATING POLES

Connectable poles with two sections, made of polyester and fibreglass tube Ø 32 mm with humidity-proof seals on each end, hand protector, grip, tip and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

Mod. BMAI-2

- Total length: 2 meters
- Composed of 2 sections of 1 m each
- Working voltage: 66 kV
- INDOOR and OUTDOOR use in dry environment

Code	Ref.
616100	BMAI-2/66M
616101	BMAI-2/66U
616102	BMAI-2/66B
616103	BMAI-2/66P

Mod. BMAI-2,5

- Total length: 2.5 meters
- Composed of 1 section of 1 m + 1 section of 1.5 m
- Working voltage: 110 kV
- INDOOR and OUTDOOR use in dry environment

Code	Ref.
616110	BMAI-2,5/110M
616111	BMAI-2,5/110U
616112	BMAI-2,5/110B
616113	BMAI-2,5/110P

Mod. BMAI-3

- Total length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 132 kV
- INDOOR and OUTDOOR use in dry environment

Code	Ref.
616120	BMAI-3/132M
616121	BMAI-3/132U
616122	BMAI-3/132B
616123	BMAI-3/132P

