

531 SGM

Composite insulated gloves provide electrical, mechanical and arc-flash protection, and as such do not need to be combined with any other kind of glove with mechanical protection.

The Composite glove range is made using a natural latex base covered by an outer layer of polychloroprene, combining mechanical resistance and comfort with a high level of protection.

Arc flash protection: the glove material has excellent properties in the event of a short circuit in the electric arc.



Ava

(€ ★ IEC 60903 IEC 61482-1-2

Available in sizes: 7, 8, 9, 10, 11 and 12

Outside in	red
and beige	inside

Code	Ref.	Class	Thickness (mm) max.	Working Voltage (V) max.	Proof test Voltage (V) max.	Size	Length (mm)	Category
531110 531120	SGM-25 T9 SGM-25 T10	00	< 2.4	500 V AC	2.500 V AC	7* 8* 9 10 11 12*	360	RC
531150 531160	SGM-50 T9 SGM-50 T10	0	< 2.9	1.000 V AC	5.000 V AC		360 410	
531190 531200	SGM-10 T9 SGM-10 T10	1	< 3.4	7.500 V AC	10.000 V AC			
531230 531240	SGM-20 T9 SGM-20 T10	2	< 3.9	17.000 V AC	20.000 V AC			
531270 531280	SGM-30 T9 SGM-30 T10	3	< 4.2	26.500 V AC	30.000 V AC			
531310 531320	SGM-40 T10 SGM-40 T11	4	< 4.8	36.000 V AC	40.000 V AC		410	

Meaning of letters in 'Categories': A: Acid / Z: Ozone / H: Oil / C: Very low temperature / R: A+Z+H resistance. *For sizes 7, 8 and 12 consult.

MECHANICAL AND THERMAL REQUIREMENTS

- Average tensile strength: ≥16 MPa
- Average elongation at break: ≥600%
- Tension set: ≤15%
- Complementary test and performance levels to be achieved are as follows:
- Resistance to cutting: > 20 mm and 5N, according to ISO13997
- Resistance to abrasion: ≥0,05 mg/t
- Tearing resistance to: >25 N (equivalent to level 2 according to EN 388)

- Resistance to penetration: >60 N (equivalent to level 2 according to EN 388)
- \blacksquare Resistance to very low temperatures: Conditioning of the gloves for 24 hours at -40 °C. \pm 3°C.
- Flame-retardant test: Application of a flame for 10 seconds at a finger tip



RECOMMENDED SIZE	9	10	11
Contour cm (measured with closed hand)	21	24	26

