IEC Electronic Voltage Detector

Voltage Detectors

Medium voltage detector - Outdoor

SAFETY CATALOGUE

POWER LIGHT

Electronic voltage detector Medium Voltage - Optical & Acoustic

Optical & Acoustic

MORE VOLTAGE RANGES from 1 to 5 kV or from 5 to 79 kV

Voltage presence indicator through multiple light indicators and intermittent acoustic signal through buzzer.

Absence of voltage indicator with high-brightness green LED over 360°. Push-button self-verification device.

Interruption of operation with low battery.

Temperature range: from -25°C to +55°C.

Indoor and outdoor use using an insulating pole suitable for the voltage range of the detector.

Union to the pole through Universal connection.

Supplied in a metal case with batteries included. (2xAAA) Alternative use as a flashlight for dark areas.

Manufactured according to IEC 61243:2003+A1:2009 and UNE-EN 61243-1:2006+A1:2011 standards (except voltage range).

645 POWER-1/5

5 KV - 50/6

1) sofamel

- Rated voltage: from 1 to 5 kV
- Frequency: 50 / 60 Hz

Oada Daf	645280	POWER-1/5
	Code	Ref.

645 POWER-5/79

- Rated voltage: from 5 to 79 kV
- Frequency: 50 / 60 Hz

Code	Ref.
645285	POWER-5/79
CE A	