

Clack™ 

**WS2  
CI**

## **WATER SPECIALIST 2" CI CONTROL VALVE**



Optional 2" Meter

- **2" Top mount control valve suited for commercial/industrial applications**
- **Lead free brass construction**
- **Economical stainless steel optional meter assembly**
- **Service flow rate of 435 lpm (26.1 m<sup>3</sup>/h) (115 gpm), backwash 303 lpm (18.2 m<sup>3</sup>/h) (80 gpm)**
- **Solid state microprocessor with easy access front panel settings**
- **Front panel display for time of day, days until next regeneration, volume remaining and current flow rate.**
- **Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential**
- **Program in ppm, French degrees, German degrees, or cubic meters**
- **Fully programmable regeneration cycle sequence (maximum 9)**
- **Programmable regeneration cycle times**
- **Days override feature; 1-28 days available**
- **Coin Cell Lithium battery back-up with an 24 hour carry over**
- **12-volt output AC Adapter provides safe and easy installation**
- **Pre or Post treated water regenerant refill**
- **24 Hour Clock**
- **Reliable and proven DC drive**

# Water Specialist 2" CI Control Specifications

Inlet/Outlet (1) .....	2" Female BSPT or NPT
Cycles .....	up to 9
Valve Material .....	Lead free brass
Regeneration .....	Downflow

## CONTROL VALVE FLOW RATES

Service @ 1 bar/15 psi drop .....	435 lpm (26.1 m <sup>3</sup> /h) (115 gpm)
Backwash @ 1.7 bar/25 psi drop.....	303 lpm (18.2 m <sup>3</sup> /h) (80 gpm)
Cv Service .....	29.7
Cv Backwash .....	16.0

## OPERATING PRESSURES

Minimum/Maximum .....	1.4 - 8.6 bar (20 psi - 125 psi)
-----------------------	----------------------------------

## OPERATING TEMPERATURES

Minimum/Maximum .....	4° - 43° C (40° - 110° F)
-----------------------	---------------------------

## METER SPECIFICATIONS

Accuracy .....	± 5%
Flow Rate Range.....	5.7 - 568 lpm (1.5 - 150 gpm)
Volume Range .....	0.02 - 5,700 m <sup>3</sup>
Totalizer .....	1 - 99,999 m <sup>3</sup> (264 - 26,417,000 gallons)

## DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 2" Female BSPT Inlet & Outlet.....	50mm OD
Valve bodies with 2" Female NPT Inlet & Outlet .....	1.90" OD (1.5" NPS)
Drain Line Connection .....	1.5" Female NPT
Brine Line Adapters Included.....	1" Male NPT elbow, ¾" x 1" solvent weld elbow and ½" OD Poly Tube Compression
Mounting Base .....	4" - 8 UN
Height From Top Of Tank.....	216 mm (8.5")
Shipping Weight With Meter .....	13 Kg (29 lbs.)

## ELECTRICAL SPECIFICATIONS

	AC Adapter	
	International	U.S.
Supply Voltage .....	230V AC.....	120V AC
Supply Frequency .....	50 Hz.....	60 Hz
Output Voltage .....	12V AC.....	12V AC
Output Current .....	500 mA.....	500 mA

## TANK APPLICATIONS

Water Softener .....	12" - 48" diameter
Water Filter (2).....	12" - 36" diameter

## CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 120 minutes
Rinse.....	1 - 120 minutes
Pause (service).....	1 - 480 minutes
Brine (co-current).....	1 - 180 minutes
Refill (softener).....	0.1 - 99.0 minutes
Refill (filter) .....	0.1 - 99.0 minutes

### Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot

2. Filter tank size calculated @ 407 lpm per m<sup>2</sup> of bed area /10 gpm of backwash per square foot of bed area