



AGRICULTURAL IMPLEMENT

- Designed with low section profile for lesser soil compaction
- Specially designed for drive and free rolling wheels
- Strengthened casing for higher load capacity

| SIZE | TYPE | RIM (inch) | INFLATED DIMENSIONS (mm) +/-2% | | | LOAD CAPACITY (kg) FOR FREE ROLLING WHEEL | | | |
|------------------|------|---------------|--------------------------------|-----|------------|---|-------------|------------------|-------------|
| | | | | | | 30 kmph with HLV | | 40 kmph with HLV | |
| | | | OD | CSW | PLY RATING | LOAD CAPACITY | IP (bar) | LOAD CAPACITY | IP (bar) |
| 10.0/80-12 | TL | 9.00 | 710 | 270 | 8 | 1500 | 4.2 | 1250 | 4.0 |
| 10.0 / 75 - 15.3 | TL | 9.00 | 760 | 264 | 10 | 1800 | 5 | 1550 | 5.1 |
| 11.5 / 80 - 15.3 | TL | 9.00 | 850 | 290 | 12 | 2575 | 5.5 | 2180 | 5.3 |
| 12.5 / 80 - 15.3 | TL | 9.00 | 890 | 305 | 14 | 3075 | 5.7 | 2650 | 5.6 |