



TAP-DOUBLE-SET

Item Number 4687789

The new wireless digital temperature and pressure gauge set is a user-friendly instrument that measures temperature and pressure (high and low pressure side) of air conditioning and refrigeration systems.

- Fast and easy connection to pressure source and temperature measuring point
- The cordless K-type temperature pliers are suitable for pipe diameters from 6 - 41 mm ($1/4''$ bis $1\ 5/8''$)
- Measurement and calculation of superheat and subcooling can be displayed on the device display as well as on the mobile phone
- Up to 6 TAP devices can be monitored simultaneously on the mobile phone
- Create report on Smart Phone and simply send it via e-mail to the office
- operation with AAA batteries
- In a sturdy plastic case, as double set

Technical Data

Material	Brass ABS TPE
Colour	yellow (RAL 1023) green (RAL 6026)
RoHS Conformity	1
RoHS Conformity	Yes
Refrigerant(s)	R11 R113 R114 R123 R124 R13 R13B1 R134a R22 R23 R32 R290 R401A R401B R402A R402B R403B R404A R406A R407A R407B R407C R407F R408A R409A R410A R413A R414B R416A R417A R420A R422A R422B R422C R422D R427A R437A R438A R448A R449A R450A R452A R500 R502 R503 R507 R508A R508B R513A R600a R744 R1233zd R1234yf R1234ze R12
Accuracy Class	1.0 (+/-1% FS)
Gas Connection	1/4" SAE

Acknowledged globally



Pressure Scale	bar psi kPa MPa
Temperature Range	0 - 50 °C
Storage Temperature Range	-20 - 60 °C
Pressure Range	-0.95 - 60 bar
Resolution	0.07 bar, 0.1 psi, 7 kPa, 0.007 MPa
Battery	3 x AAA 4 x AAA
Operating Hours	40h / 50h
Signal Range	30 m
Functions	Superheat / Subcool, Pressure zeroing, Refrigerant favorites Auto off Unit and language settings, Update refrigerants, Calibration of WIRELESS-CLAMP WTC and TAP pressure gauge, Wireless connections
Packaging	Sturdy plastic case
Sensor Type	K-type Piezo Sensor
Temperature Range	-40°C - + 125 °C
Temperature Units	°C °F
Temperature Accuracy	+/-1 K
Temperature Resolution	0.1 °C / 0.1 °F
Scope of Supply	2 TAP Pressure Gauge, 2 WIRELESS-CLAMP WTC, 2 SAE 1/4" female/female adapter, 1 USB Cable, 14 Batteries, 1 Manual, 1 Case

Accessories

9881265	CL-6-R	Charging hose, red, 1/4"SAE, 6"/15 cm 1x straight 1/4" SAE,
---------	--------	---

Acknowledged globally



		1x bended 1/4" SAE with core depressor
9881256	CL-6-B	Charging hose, blue, 1/4"SAE, 6"/15 cm 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4687824	QC-S4A-5/16"SAE/2	Quick coupler straight 1/4"SAEx5/16"SAE, 2 pcs.
4687631	SWIVEL-ARM-1/4"SAE-N	Swivel arm for vacuum gauge, 1/4" SAE
4687095	QC-S410A/2	Adapter with core depressor, 1/4" SAE x 5/16" SAE, 2 pieces

Spare Parts

4687787	TAP	Pressure Gauge
4687785	WIRELESS-CLAMP WTC	Temperature clamp for REFMATE and TAP
4687823	QC-S4A-1/4"SAE/2	Quick coupler straight 1/4" SAEx1/4"SAE, 2 pcs.
4687793	TAP-MARKING-RING-SET	Marking rings for TAP 4x2 pcs per size, blue and red
4687859	TAP-DOUBLE-SET-CASE	Case for TAP-DOUBLE-SET