

SMALL BUT POWERFUL

The **RED PANTHER** range of dry powder extinguishers is certified to BS EN: 1996 and manufactured under an ISO 9001 approved Quality system.

The cylinders are deep drawn from cold rolled steel, center welded and pressure tested to twice the extinguisher's working pressure.

Cylinder are externally coated with epoxy polyester (with phosphate under treatment) for maximum corrosion resistance and have passed the 480-hour salt spray test. The hot forged brass valve is fitted with a press can be tested ' in-service' as required by BS EN 3:1996.

The **RED PANTHER** range of dry powder FEs is charge with specially fluidized and siliconised mono ammonium phosphate powder which offer resistance to compaction where the extinguisher is installed in a location subjected to vibration and are safe and effective for use on Class A, B, and C fires under BS EN3: 1996 classification of fires.



Anti Rust Easy to use **Light & Portable** Easy to maintain No costly servicing



Design & Maufacture to: BS FN 3-1966

Working Temp.Range: -20°C to +60°C

Extinguishant: ABC Dry Powder Properllant: Dry Nitrogen (N2) Overall Height(mm): 322mm

Coating(Internal): Stoving Epoxy Primer

Text Pressure: 25 BAR

Fire Rating: 5A 34B

Paint Fishing: Signal Red (RAL3000)

Epoxy Polyester Powder Coating