

Z1000


BLACK

BLACK (R EDITION)

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke In-Line Four, DOHC, 16 Valves	Type	Twin-tube, aluminium
Displacement	1043 cm ³	Caster (rake)	24.5°
Bore and Stroke	77.0 x 56.0 mm	Tyre:	
Compression Ratio	11.8:1	a) Front	120/70ZR17M/C (58W)
Performance:		b) Rear	190/50ZR17M/C (73W)
a) Maximum power	104.5 kW {142 PS} / 10,000 min ⁻¹	SUSPENSION	
b) Maximum torque	111.0 N.m {11.3 kgf.m} / 7,300 min ⁻¹	Front: Type	ø41 mm inverted fork with compression and rebound damping and spring preload adjustability
Fuel System	Fuel injection ø38 X 4 with oval sub-throttles	Rear: Type	Horizontal Back-link, gas charged shock with rebound damping and spring preload adjustability Horizontal Back-link, Öhlins S46DR1S gas-charged shock with rebound damping and spring preload adjustability (Special Edition)
Ignition	Digital	BRAKES	
Starting	Electric	Front: Type	Dual semi-floating ø310mm petal discs Dual semi-floating ø310mm Brembo discs (Special Edition)
Lubrication	Forced lubrication, wet sump	Caliper	Dual radial-mount, monobloc, opposed 4-piston Dual radial-mount, Brembo M50 monobloc, opposed 4-piston (Special Edition)
DRIVETRAIN		Rear: Type	Single ø250 mm petal disc Single ø250 mm disc (Special Edition)
Transmission	6-speed, Return	Caliper	Single-piston
Finaldrive	Chain	DIMENSIONS	
Gear ratios:		Overall length	2,045 mm
1st	2.600 (39/15)	Overall width	790 mm
2nd	1.950 (39/20)	Overall height	1,055 mm
3rd	1.600 (24/15)	Wheelbase	1,435 mm
4th	1.389 (25/18)	Ground clearance	125 mm
5th	1.238 (26/21)	Seat height	815 mm
6th	1.107 (31/28)	Curb mass	221 kg
Final reduction ratio	2.867 (43/15)	Fuel capacity	17 litres
Clutch	Wet multi-disc, manual		