



## LED-30 TWIN-LAMP SELF-CONTAINED EMERGENCY LIGHTING LUMINAIRE

### Technical Data

Mode of Operation	: Non-Maintained.
Input Voltage	: 240V $\pm$ 10%, 50Hz
Battery	: Hi-Temp. Nickel Cadmium Battery.
Charging Current	: 80mA (Nominal).
Lamp Used	: 2 x 15 Super Bright White LED.
Operating Temperature	: 0°C to 60°C
Charger	: Fully Automatic Constant Current. Solid-State Electronics Provide High Reliability with Trickle Charge-Facility.
Indication	: Red L.E.D. "On" Indicates Charging. Equipped with Push Test-Switch to Simulate Power Failure.
Backup Time	: 3 Hours Duration.
Construction	: Injection Moulded Fire-Retardant Polycarbonate Housing with Rear Knockout Cable Entry. Injection Moulded Fire-Retardant Polycarbonate Diffuser.
Weight	: $\pm$ 0.8kg
#Warranty	: 5 Years.
Compliance	: Malaysia Standards MS-619, IP-20.
Protection	: Low-Voltage Cut-Off to Prevent Over-Discharge of Battery.

Dimension in mm  
Tolerance:  $\pm$  0.03 mm

#### Wall Mounting

