

RICOH
imagine. change.

Lightweight, compact projectors

RICOH
PJ WX2240
PJ X2240
PJ S2240



3,000lm/
3,100lm

Compact
design
2.6kg

High
contrast
ratio
10,000:1

4,500hrs
lamp life

HDMI
3D Ready

23
languages
OSD

Ricoh projectors provide high quality presentations

RICOH PJ WX 2240/PJ X2240/PJ S2240 lightweight and compact projectors combine all the advanced functionality, reliability and value for money you expect from Ricoh. While small, these projectors pack a big punch with 3,000 lumens brightness (3,100 for RICOH PJ WX2240), high contrast levels and long lamp life. Designed to be durable and simple to use, these versatile projectors are easily carried for set up in any convenient location. The remote control makes operation easy and the wide choice of interface connections including HDMI, allows input from a range of devices for maximum flexibility.

- Lightweight, compact and easily carried for convenient location
- Durable with long lamp life up to 6,000 hours in eco mode
- Bright, high contrast resolution for clear presentations
- Simple operation with remote control for convenient use
- Wide selection of interfaces for versatile choice of device input



Easy to operate, feature rich projectors

Outstanding image quality

Image quality is assured with 3,000 lumens brightness for the RICOH PJ X2240 and PJ S2240 (XGA/SVGA) so the projector can be placed from 1 to 12 metres distance from the screen. The WXGA format PJ WX2240 model has 3,100 lumens brilliance. Image brilliance is matched by high contrast of 10,000:1, providing clear, vivid images and deeper blacks that will enhance any presentation-like text and graphs.

Lightweight and easy to use

Weighing only 2.6kg, these compact projectors have a footprint just larger than an A4 sheet of paper, making them highly portable for fast set-up anywhere there is a power outlet. Operation is easy with a remote control to give full management of features and functions. The in-built speaker on the PJ X2240 and PJ WX2240 models means that no external sound system is required for presentations.



Flexible choice of device interfaces

All the models have the latest HDMI interface allowing high quality image projection including 3D content (optional 3D glasses required), futureproofing your investment. The PJ WX2240 and PJ X2240 models have input ports for two computers as well as an output port to a monitor and an audio-out connection for linking to an external sound system, if required. The PJ S2240 can connect one computer and all models have a port for PC Control (RS232).



Designed to be durable for maximum reliability

This highly versatile range of projectors has been designed to be durable, requiring the minimum of maintenance. Lamp life is 4,500 hours in standard mode and using the EcoMode feature lowers lamp brightness, reducing energy consumption and can extend lamp life by over 30% to 6,000 hours. Ricoh is the brand you can trust and the robust design of these projectors ensures low Total Cost of Ownership.

RICOH PJ WX2240/ PJ X2240/ PJ S2240

MAIN SPECIFICATIONS

GENERAL

| | |
|---|---|
| Projection system: | Single-chip DLP |
| Resolution: | PJ WX2240: 1,024,000 pixels (1,280 x 800) PJ X2240: 786,432 pixels (1,024 x 768) PJ S2240: 480,000 pixels (800 x 600) |
| Panel: | PJ WX2240: 0.65 inch PJ X2240: 0.55 inch PJ S2240: 0.55 inch |
| Brightness: | PJ WX2240: 3,100 lumen PJ X2240: 3,000 lumen PJ S2240: 3,000 lumen |
| Colour reproducibility: | 1,073,000,000 colours |
| Contrast ratio (Native): | PJ WX2240: 2,000:1 PJ X2240: 2,200:1 PJ S2240: 2,200:1 |
| Contrast ratio (High contrast mode): | 10,000:1 |
| Projection screen size: | 30" to 300" |
| Projection distance: | PJ WX2240: 1.0 to 10.0 m PJ X2240: 1.2 to 12.0 m PJ S2240: 1.2 to 12.0 cm (from rear of unit to projection surface) |
| Throw ratio: | PJ WX2240: 1.55-1.7 PJ X2240: 1.95-2.15 PJ S2240: 1.95-2.15 |
| Lamp: | High-pressure mercury lamp |
| Lamp life: | Standard: 4,500 hours (190 W) Eco mode 1: 6,000 hours (190 W) |
| RGB compatible signals (analogue, digital): | Real display: PJ WX2240: WXGA, XGA, SVGA, VGA PJ X2240: XGA, SVGA, VGA PJ S2240: SVGA, VGA Compressed representation: PJ WX2240: UXGA, SXGA PJ X2240: UXGA, SXGA, WXGA PJ S2240: UXGA, SXGA, WXGA, XGA |
| Input signals: | NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-60, 60Hz, 50Hz |
| Analogue RGB compatible scanning frequency: | Horizontal: 30 to 100 kHz Vertical: 50 to 85 Hz, 120 Hz for 3D mode |
| Zoom ratio: | 1.1 (manual) |
| Connection terminal (PJ WX2240/PJ X2240): | Mini D-SUB15pin x 3 (Computer 1 IN, Computer 2 IN, Monitor OUT), Mini DIN 4pin x 1, RCA 1pin x 1, D-SUB 9pin x 1 (RS-232C), Mini Jack x 3 (Audio1 IN, Audio2 IN, Audio OUT), USB-TYPE-minB x1, HDMI(1.4) x 1 |
| Connection terminal (PJ S2240): | Mini D-SUB15pin x 1 (Computer 1 IN), Mini DIN 4pin x 1, RCA 1pin x 1, D-SUB 9pin x 1 (RS-232C), USB-TYPE-minB x1, HDMI(1.4) x 1 |

| | |
|--|--|
| Primary features: | Mute (Blank), Freeze, Re-size (Magnify), Eco mode, 3D projection (Ready), Wall color mode, Security bar, Kensington lock |
| Built-in speaker (PJ WX2240/PJ X2240): | 2 W mono |
| Dimensions (W x D x H): | 314.2 x 223.5 x 101.7 mm |
| Weight: | 2.6 kg |
| Supported languages: | English, German, French, Italian, Spanish, Dutch, Swedish, Norwegian, Danish, Finnish, Hungarian, Czech, Polish, Portuguese, Russian, Japanese, Korean, Traditional Chinese, Simplified Chinese, Turkish, Arabic, Indonesian, Thai |
| Power source: | 100 - 240 V, 50/60 Hz |

ECOLOGY

| | |
|------------------------|--|
| Power consumption: | Operating power: 267 W Energy Saver mode: 224 W Stand-by mode: 0.5 W |
| Operating temperature: | 5°C - 40°C |
| Operating humidity: | 80% |
| Storage conditions: | Temperature: 20 - 60°C |
| Noise level: | Standard: 34 dB Eco: 31 dB |

ACCESSORIES

RGB cable, Power cable, CD-ROM and manual, Remote control with batteries, Lens cap, Carrying case (PJ WX2240/PJ X2240)

OPTIONS

RICOH PJ 3D glasses Type 2

CONSUMABLES

Replacement lamp Type 14

For availability of models, options and software, please consult your local Ricoh supplier.

RICOH
imagine. change.

www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467
Phone: +65 6830 5888, Fax: +65 6830 5830