

**Description**

Cascadable multiswitches for 4 polarities and terrestrial TV with 20, 24 and 30 outputs. The outputs are amplified in the satellite IF band. In the terrestrial band they can be configured to function in either active or passive mode. Need to be powered from each individual receiver so that the switching and amplification of each derived output will function.

Applications

Medium-sized collective satellite and terrestrial TV installations. It is essential that they be mounted along with end multiswitches, so as to obtain distributions of up to 128 outlets on a single line if they are installed with intermediary amplifiers.

Characteristics

Shielded metal chassis with plastic supports. F-type connectors. Earth.

Accessories

9090033 AV-315 Variable attenuator, 5-2400 MHz, 18 dB with DC path.
 9090029 PR-310 Preamplifier, 5-2400 MHz, 10 dB with DC path.
 9090038 BL-300 Current blocker.

CODE	9130152	9130153	9130159				
MODEL	ML-105	ML-106	ML-108				
TV system		FM-TV / DVB-S / AM-TV / DVBT					
Connection		F female					
Inputs/outputs		5/5					
Tap outputs	20	24	32				
Frequency range	MHz	47-862 950-2150	47-862 950-2150				
PASSIVE MODE							
Tap loss	dB±TOL	25 ±3.0	-1 ±4.0	25 ±3.0	-1 ±4.0	25 ±3.0	-1 ±2.0
Output level	dB _p V	-	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)	-	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)	-	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)
ACTIVE MODE							
Tap loss	dB±TOL	5 ±3.0	-1 ±4.0	5 ±3.0	-1 ±4.0	5 ±2.0	-1 ±2.0
Output level	dB _p V	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)
ACTIVE / PASSIVE MODE							
Tap equalization	dB	7	4	7	4	7	3
Rejection between bands	dB				> 20 TV/SAT > 65 SAT/TV		
Isolation between users	dB				> 20 TV > 20 SAT		
Isolation of switching	dB				> 30 SAT/SAT		
Switching the outputs				DiSEqC 2.0 14V.../18V... 0/22 kHz			
Power supply of the LNB				1050 mA /13 V...			
Output voltage	V...			13 V...			
Consumption from the receiver	mA			42 ±2.0 (14/18V...)			
Operating temperature close to equipment	°C			-10..+65			
Room temperature with/without fan	°C			-10..+55/+45			
Protection index				IP 30			
Units per packing		1	5	1	5	1	5
Packing weight	Kg	0.56	3.30	0.58	3.40	0.78	4.40
Packing dimensions	mm	260 x 245 x 55	290 x 270 x 270	260 x 245 x 55	290 x 270 x 270	330 x 245 x 55	345 x 305 x 270

IMD₃ -35 dB: 2 equal carriers, EN 50083-5

IMD₂ -35 dB: 2 equal carriers, EN 50083-5

Data published in compliance with the definitions and measurement methods of the following standards: EN 50083-3, EN 50083-4 and EN 50083-5