



Beta Three

TS300

TS SERIES | 12" Two Way Full Range Speaker

Product Description:

Portable and installed plastic loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The TS Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 12" high power transducer with 50mm voice coil
- 1 x 1.3" diaphragm compression driver
- 90° x 60° controlled coverage pattern
- Heavy duty protective grill
- Injection molded
- 2 x NL4 connector
- Cabinet design for FOH and Monitor use
- Suitable for use as a main system with or without sub speaker augmentation
- Portable system (stand), or permanent installation (wall, ceiling)
- Integrated stand mount
- Monitor kit - optional



System Specifications:

Construction	Plastic
Transducers	1 x 1.3" HF + 1 x 12" LF
Frequency Response (-3dB)	50Hz-20kHz
Rated Power	300W (RMS)
Sensitivity (1W @ 1m)	96dB
Rated Impedance	8Ω
Dispersion (H x V)	90° x 60°
Connector	2 x NL4
Dimensions (W x D x H)	320mm (12.6") x 430mm (16.9") x 580mm (22.8")
Packaging Dimensions (1 piece/pack)	360mm (14.2") x 460mm (18.1") x 650mm (25.6")
Net Weight (1 piece/pack)	18kg (39.7lb)
Gross Weight (1 piece/pack)	20.2kg (44.5lb)

