

EC type examination certificate

CERT

EG-Baumusterprüfbescheinigung

CE-0085AQ0882

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Pressure Equipment Directive (2014/68/EU) EG-Druckgeräterichtlinie (2014/68/EU)
Owner of Certificate <i>Zertifikatinhaber</i>	MEDENUS Gas-Druckregeltechnik GmbH Saßmicker Hammer 40, D-57462 Olpe
Distributor <i>Vertreiber</i>	MEDENUS Gas-Druckregeltechnik GmbH Saßmicker Hammer 40, D-57462 Olpe
Product Category <i>Produktart</i>	gas fittings: Pressure regulator for natural gas and all-gas (4301)
Product Description <i>Produktbezeichnung</i>	Pressure regulator optional with safety shut-off valve (SAV) for upper and lower shut down pressure and/or pilot support
Model <i>Modell</i>	R/RS/RP/RSP 250, R/RS/RP/RSP 254
Test Reports <i>Prüfberichte</i>	type testing: 17/304/4308/210 v2 from 21.12.2017 (EBI)
Test Basis <i>Prüfgrundlagen</i>	2014/68/EU A III B Baumusterprüfung (15.04.2014) DIN EN 334 (01.07.2009) DIN EN 14382 (01.07.2009)


Date of Expiry / File No. 31.07.2022 / 17-0815-GDA
Ablaufdatum / Aktenzeichen

17.04.2018 Kö A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of pressure equipment under EC Directive

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Druckgeräten und Baugruppen gemäß Richtlinie




DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases and non-aggressive gases	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 25	
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 50	
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 80	
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 100	
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 150	
R/RS/RP/RSP 250, R/RS/RP/RSP 254	nominal diameter: DN 200	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
R	pressure regulator
RS	pressure regulator with SAV
RP	pressure regulator with pilot support (pilots R70-10, R70-20, R70-100 and for the SAV K70-10)
RSP	pressure regulator with SAV and pilot support
R/RS/RP/RSP 250	max. allowable pressure: PS = 8 bar, nominal pressure PN 8
R/RS/RP/RSP 254	max. allowable pressure: PS = 16 bar, nominal pressure PN 16
R/RS/RP/RSP 250; R/RS/RP/RSP 254	temperature range: -20°C to +60°C, class 2

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

connection: both sides flanges PN 16 acc. DIN EN 1092-4 or ASME B 16.5 Class 150 RF
accuracy class AC/ lock up pressure group SG, pressure regulator without pilot:
18...100 mbar: AC 10/SG 20
100...500 mbar: AC 5/SG 10
500...1500 mbar: AC 2,5/SG 10
>1000 mbar: AC 5/SG 10 (with regulator device 205/275-2)
accuracy class AC/ lock up pressure group SG, pressure regulator with pilot:
10...20 mbar: AC 10/SG 50
20...50 mbar: AC 5/SG 20
50...500 mbar: AC 5/SG 10
500...2500 mbar: AC 2,5/SG 10
2500...5000 mbar: AC 1/SG 10
>5000 mbar: AC 1/SG 5
upper response group AG of safety shut off valve:
50...100 mbar: AG 10
100...500 mbar: AG 5
>500 mbar: AG 2,5
lower response group AG of safety shut of valve:
10...30 mbar: AG 20
30...50 mbar: AG 10
>50 mbar: AG 5
body material: aluminium casting EN AC-42100 S T6; EN AC-43000 S T6 (only DN 200); EN-GJS400-15 (only RS 250; DN 50/80/100)