



1	Magnetic shaft
2	Coil
3	Shaft
4	Upper body
5	Spring
6	Obturator
7	Body
8	Reset knob

Dimension	Flow (mc/H)	Power	A (mm)	B (mm)	Approvals	Power supply
½"	4,5	6 W	86	165	Dir.97/23/CE-EN161	12Vcc
½"	4,5	9 VA	86	165	Dir.97/23/CE-EN161	230Vac
¾"	6	6 W	86	165	Dir.97/23/CE-EN161	12Vcc
¾"	6	9 VA	86	165	Dir.97/23/CE-EN161	230Vac
1"	13	6 W	93	175	Dir.97/23/CE-EN161	12Vcc
1"	13	9 VA	93	175	Dir.97/23/CE-EN161	230Vac
1" ¼	40	6 W	114	200	Dir.97/23/CE-EN161	12Vcc
1" ¼	40	9 VA	114	200	Dir.97/23/CE-EN161	230Vac
1" ½	50	6 W	114	200	Dir.97/23/CE-EN161	12Vcc
1" ½	50	9 VA	138	210	Dir.97/23/CE-EN161	230Vac
2"	80	6 W	138	210	Dir.97/23/CE-EN161	12Vcc
2"	80	9 VA	138	210	Dir.97/23/CE-EN161	230Vac

