

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 1 / 10

Safety data sheet according to U.S.A. Federal Hazcom 2012 and Canadian Regulation SOR/88-66

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code. HI84529-52

Product name. Titratable Acidity LR Titrant

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Reagent for Measuring Titratable Acidity of Dairy Products.

1.3. Details of the supplier of the safety data sheet.

Name. Hanna Instruments S.R.L.

Full address. str. Hanna Nr 1
District and Country. 457260 loc. Nusfalau (Salaj)

Romania

Tel. (+40) 260607700 Fax. (+40) 260607700

e-mail address of the competent person.

responsible for the Safety Data Sheet. sds@hannainst.com

Product distribution by: Hanna Intruments, Inc - 584 Park East, Woonsochet, Rhode Island, USA 02895 -

Technical Service Contact Information: +1-800-426-6287

1.4. Emergency telephone number.

For urgent inquiries refer to. USA Emergency Contact Information: +1-800-424-9300 - CHEMTREC 24

hours/365 days - International Emergency Contact Information: +1-703-527-3887 -

CHEMTREC 24hours/365 days

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Substance or mixture corrosive to metals, category 1

Skin corrosion, category 1A

Serious eye damage, category 1

May be corrosive to metals.

Causes severe skin burns and eye damage.

Causes serious eye damage.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements:

Prevention:

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.



Hanna Instruments S.R.L.

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 2 / 10

SECTION 2. Hazards identification. .../>>

P310 Immediately call a POISON CENTER or doctor.

P391 Collect spillage.

Storage:

Disposal:

2.2. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. x = Conc. %. Classification:

SODIUM HYDROXIDE

CAS. 1310-73-2 1 ≤ x < 2 Substance or mixture corrosive to metals, category 1 H290, Skin corrosion,

category 1A H314

EC. 215-185-5 INDEX. 011-002-00-6 Reg. no. 01-2119457892-27

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

$\textbf{4.2.} \ \textbf{Most important symptoms and effects, both acute and delayed.}$

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

SODIUM HYDROXIDE

Irritation and corrosion, Cough, Shortness of breath, collapse, death. Risk of blindness!.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

^{*} There is a batch to batch variation.



HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 3 / 10

SECTION 5. Firefighting measures. .../>>

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).

TLV-ACGIH ACGIH 2016

SODIUM HYDROXIDE

Threshold Limit Value.							
Туре	Country	TWA/8h		STEL/15r	STEL/15min		
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-			2 (C)			
OSHA	USA	2					
CAL/OSHA	USA	2					
NIOSH	USA			2 (C)			

Legend:



Hanna Instruments S.R.L.

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 4 / 10

SECTION 8. Exposure controls/personal protection. />

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

SODIUM HYDROXIDE

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms OSHA ID-121.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid
Colour colourless
Odour odourless
Odour threshold. Not available.
pH. 13.2
Melting point / freezing point. Not available.
Initial boiling point. Not available.
Boiling range. Not available.

Flash point. > 93 °C. (199,4 °F)

Evaporation rate Not available. Flammability (solid, gas) Not available Not available. Lower inflammability limit. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Not available Vapour pressure. Vapour density Not available. 1 100 Relative density.

Solubility soluble in water
Partition coefficient: n-octanol/water Not available.
Auto-ignition temperature. Not available.
Decomposition temperature. Not available.
Viscosity Not available.
Explosive properties Not available.
Oxidising properties Not available.

9.2. Other information.

Total solids (250°C / 482°F) 1,19 %



HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 5 / 10

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

SODIUM HYDROXIDE

Hygroscopic.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

SODIUM HYDROXIDE

Risk of explosion/exothermic reaction with: Acetone, Nitriles, phosphides, halogens, halogen-halogen compounds, chlorinated solvents, Ethylene oxide, Hydrazine hydrate, hydroxylamine, anhydrides, Peroxides, Acrolein, Acid chlorides, Acids, sulphuric acid, silver salt, hydrogen peroxide, organic nitro compounds, Water, Metals, Light metals. Possible formation of: Hydrogen. Violent reactions possible with: ammonium compounds, organic combustible substances, phenols. Generates dangerous gases or fumes in contact with: persulfates, Sodium borohydride, Oxides of phosphorus.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

SODIUM HYDROXIDE

Exposure to the air, moisture and sources of heat.

10.5. Incompatible materials.

SODIUM HYDROXIDE

Strong acids, ammonia, zinc, lead, aluminium, water and flammable liquids.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

SODIUM HYDROXIDE

Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach - Acute inhalation toxicity, Symptoms: burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract - Skin irritation, Rabbit, Result: Causes severe burns - Eye irritation, Rabbit, Result: Irreversible effects on the eye, Causes serious eye damage. Risk of blindness! - Sensitisation, Patch test: human, Result: Does not cause skin sensitisation - Germ cell mutagenicity, Genotoxicity in vitro, Mutagenicity (mammal cell test): micronucleus, Result: negative, (Lit.) Ames test, Result: negative.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:

LC50 (Inhalation - mists / powders) of the mixture:

LD50 (Oral) of the mixture:

LD50 (Dermal) of the mixture:

Not classified (no significant component).

Not classified (no significant component).

Not classified (no significant component).

SODIUM HYDROXIDE

 LD50 (Oral).
 1350 mg/kg Rat

 LD50 (Dermal).
 1350 mg/kg Rat



HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 6 / 10

SECTION 11. Toxicological information. .../>>

SKIN CORROSION / IRRITATION.

Corrosive for the skin.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.

SODIUM HYDROXIDE

LC50 - for Fish. 45.4 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea. 40.38 mg/l/48h Daphnia

12.2. Persistence and degradability.

SODIUM HYDROXIDE

Solubility in water. > 10000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

SODIUM HYDROXIDE

Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted. Neutralisation possible in waste water treatment plants. Discharge into the environment must be avoided.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.



HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 7 / 10

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 1824

14.2. UN proper shipping name.

ADR / RID: SODIUM HYDROXIDE SOLUTION IMDG: SODIUM HYDROXIDE SOLUTION IATA: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es).

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: 80 Limited Quantities: 5 L Tunnel restriction code: (E)

Special Provision: IMDG: EMS: F-A, S-B Limited Quantities: 5 L

IATA: Cargo: Maximum quantity: 60 L

Cargo: Maximum quantity: 60 L Packaging instructions: 856 Pass.: Maximum quantity: 5 L Packaging instructions: 852

Special Instructions: A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):
No component(s) listed.



Hanna Instruments S.R.L.

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 8 / 10

SECTION 15. Regulatory information. .../>>

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

1310-73-2 SODIUM HYDROXIDE

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.

Massachussetts:

1310-73-2 SODIUM HYDROXIDE

Minnesota:

1310-73-2 SODIUM HYDROXIDE

New Jersey:

1310-73-2 SODIUM HYDROXIDE

New York:

1310-73-2 SODIUM HYDROXIDE

Pennsylvania:

1310-73-2 SODIUM HYDROXIDE

California:

1310-73-2 SODIUM HYDROXIDE

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.



Hanna Instruments S.R.L.

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 9 / 10

SECTION 15. Regulatory information. />>

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Met. Corr. 1 Substance or mixture corrosive to metals, category 1

Skin Corr. 1A
Eye Dam. 1
H290
Skin corrosion, category 1A
Serious eye damage, category 1
May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597



Hanna Instruments S.R.L.

HI84529-52 - Titratable Acidity LR Titrant

Revision nr.1 Dated 12/16/2016 Printed on 12/19/2016 Page n. 10 / 10

SECTION 16. Other information. .../>>

- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.