

HI96707B - Cal Check® Standard Cuvette B

Safety data sheet according to SOR/88-66	U.S.A. Federal Hazcom 2012 and Canadian Regulation
SECTION 1. Identification of the s	ubstance/mixture and of the company/undertaking.
1.1. Product identifier.	
Code. Product name.	HI96707B Cal Check® Standard Cuvette B
1.2. Relevant identified uses of the substance	or mixture and uses advised against.
Intended use.	Validation and Calibration of Hanna Portable Photometers that Measure LR Nitrite.
1.3. Details of the supplier of the safety data s	heet.
Name. Full address. District and Country.	Hanna Instruments S.R.L. str. Hanna Nr 1 457260 loc. Nusfalau (Salaj) Romania Tel. (+40) 260607700 Fax. (+40) 260607700
e-mail address of the competent person. responsible for the Safety Data Sheet.	sds@hannainst.com
Product distribution by:	Hanna Intruments, Inc - 584 Park East, Woonsochet, Rhode Island, USA 02895 - Technical Service Contact Information: +1-800-426-6287
1.4. Emergency telephone number.	
For urgent inquiries refer to.	USA Emergency Contact Information: +1-800-424-9300 - CHEMTREC 24 hours/365 days - International Emergency Contact Information: +1-703-527-3887 - CHEMTREC 24hours/365 days
SECTION 2. Hazards identification	n.
2.1. Classification of the substance or mixture	
1910.1200). The product thus requires a safet	rsuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR y datasheet. s for health and/or the environment are given in sections 11 and 12 of this sheet.
Classification and Hazard Statement. Substance or mixture corrosive to metals, category 1 Carcinogenicity, category 1B Germ cell mutagenicity, category 2 Reproductive toxicity, category 1B Skin corrosion, category 1B Eye irritation, category 2 Respiratory sensitization, category 1 Skin sensitization, category 1	May be corrosive to metals. May cause cancer. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes severe skin burns and eye damage. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Hazard pictograms:



Signal words:

H341 H360

H314 H334

Danger

Hazard statements: H290 H350 May be corrosive to metals. May cause cancer. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.



HI96707B - Cal Check® Standard Cuvette B

SECTION 2. Hazards identification. ... / >>

SECTION 2. Hazards id	entification /	>>				
H317	May cause an allergic ski	n reaction.				
Precautionary statement	s'					
Prevention:						
P201	Obtain special instruction					
P260 P273		Do not breathe dust, fume, gas, mist, vapours, spray. Avoid release to the environment.				
P280		rotective clothing, eye protection and face protection.				
Response:	IF ON SKIN: Wash with plenty of water and soap. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing.					
P305+P351+P338 P308+P313 P333+P313 P342+P311 P342+P311	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice / attention. If skin irritation or rash occurs: Get medical advice / attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor.					
P391	Collect spillage.					
Storage:						
Disposal:						
2.2. Other hazards.						
Environmental classifica	tion as for Reg. (EU)	1272/2008 (CLP):				
The product is classified	as hazardous for env	vironment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).				
Classification and Hazar Hazardous to the aquatic en		category 2 Toxic to aquatic life with long lasting effects.				
Hazard pictograms:						
¥2						
Hazard statements: H411	Toxic to aquatic life with le	ong lasting effects.				
Precautionary statement	S:					
Prevention:						
Response:						
Storage:						
Disposal:						
Additional hazards. Information not available						
SECTION 3. Composition/informat	ion on ingredients.					
3.1. Substances.	J					
Information not relevant.						
3.2. Mixtures.						
Contains:						
Identification.	x = Conc. %.	Classification:				
COBALT (II) CHLORIDE HEXA	HYDRATE					
24,79% - metallic element CAS. 7791-13-1	1≤x< 2.5	Carcinogenicity, category 1B H350, Germ cell mutagenicity, category 2 H341, Reproductive toxicity, category 1B H360F, Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Serious eye damage, category 1 H318, Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317, Hazardous to the aquatic environment,				
EC. 231-589-4 INDEX. 027-004-00-5		acute toxicity, category 1 H400 M=10, Hazardous to the aquatic environment, chronic toxicity, category 1 H410 M=1				

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017

Page n. 2 / 12



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 3 / 12

SECTION 3. Composition/information on ingredients./>>

HYDROCHLORIC ACID CAS. 7647-01-0

7647-01-0 1 ≤ x < 3

Substance or mixture corrosive to metals, category 1 H290, Skin corrosion, category 1B H314, Specific target organ toxicity - single exposure, category 3 H335

EC. 231-595-7 INDEX. 017-002-01-X Reg. no. 01-2119484862-26

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

HYDROCHLORIC ACID

HYDROCHLORIC ACID 37%: Irritation and corrosion, Cough, Shortness of breath, cardiovascular disorders, Risk of blindness!. COBALT (II) CHLORIDE HEXAHYDRATE Allergic reactions, irritant effects, Diarrhoea, Tremors, Symptoms of an acute cobalt intoxication: diarrhoea, loss of appetite, drop in body

temperature, drop in blood pressure. Toxic effect on kidneys (proteinuria, anuria), heart, and pancreas.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

HYDROCHLORIC ACID

HYDROCHLORIC ACID 37%: Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Hydrogen chloride gas.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



HI96707B - Cal Check® Standard Cuvette B

SECTION 6. Accidental release measures./>>

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

Threshold Limit Value

USA USA	NIOSH-REL OSHA-PEL	NIOSH publication No. 2005-149, 3th printing, 2007. Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU TLV-ACGIH	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. ACGIH 2016

COBALT (II) CHLORIDE HEXAHYDRATE

The Shora Linne	value.						
Туре	Country	TWA/8h		STEL/15			
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-	0.02					

				HYDRO	CHLORIC ACI	כ	
Threshold Limit V	alue.						
Туре	Country	TWA/8h		STEL/			
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-				2 (C)		
OEL	EU	8	5	15	10		
OSHA	USA			7 (C)	5 (C)		
CAL/OSHA	USA	7	5				
NIOSH	USA			7 (C)	5 (C)		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

HYDROCHLORIC ACID

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norm NIOSH 7903.

COBALT (II) CHLORIDE HEXAHYDRATE

Co - Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms ISO 15202 - Biological Values, ACGIH: 15 μ g/L Cobalt in urine (End of shift at end of workweek), DEU: 15 μ g/L Cobalin Urin, Luft Cobalt 0.025 mg/Kubikmeter (Expositionsende bzw. Schichtende; bei Langzeitexposition: nach mehreren vorangegangenen Schichten), ESP: 15 μ g/L Cobalto en orina (Final de la semana laboral).



HI96707B - Cal Check® Standard Cuvette B

SECTION 8. Exposure controls/personal protection. />>

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations. HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance		iiquiu			
Colour		red			
Odour			odourle	ess	
Odour threshold.			Not ava	ailable.	
pH.			0.5		
Melting point / free	zing point.		Not ava	ailable.	
Initial boiling point.			Not ava	ailable.	
Boiling range.			Not ava	ailable.	
Flash point.		>	93	°C.	(199,4 °F)
Evaporation rate			Not ava	ailable.	
Flammability (solid	l, gas)		Not ava	ailable.	
Lower inflammabil	ity limit.		Not ava	ailable.	
Upper inflammabil	ity limit.		Not ava	ailable.	
Lower explosive lir	nit.		Not ava	ailable.	
Upper explosive lir	nit.		Not ava	ailable.	
Vapour pressure.			Not ava	ailable.	
Vapour density			Not ava	ailable.	
Relative density.			1.00		
Solubility			soluble	in water	
Partition coefficient: n-octanol/water			Not ava	ailable.	
Auto-ignition temperature.			Not ava	ailable.	
Decomposition temperature.			Not ava	ailable.	
Viscosity			Not ava	ailable.	
Explosive propertie		Not ava	ailable.		
Oxidising propertie	s		Not ava	ailable.	
9.2. Other inform	nation				
Total solids (250°C			3,85 %		
			.,		

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

HYDROCHLORIC ACID HYDROCHLORIC ACID 37%: Corrosive in contact with metals.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

US



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 6 / 12

SECTION 10. Stability and reactivity. .../>>

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

COBALT (II) CHLORIDE HEXAHYDRATE Risk of explosion with: Alkali metals.

HYDROCHLORIC ACID

HYDROCHLORIC ACID 37%: Exothermic reaction with: Amines, potassium permanganate, salts of oxyhalogenic acids, semimetallic oxides, semimetallic hydrogen compounds, Aldehydes, vinylmethyl ether, Risk of ignition or formation of inflammable gases or vapours with: carbides, lithium silicide, Fluorine, Generates dangerous gases or fumes in contact with: Aluminium, hydrides, formaldehyde, Metals, strong alkalis, Sulphides. Risk of explosion with: Alkali metals, conc. sulfuric acid.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

HYDROCHLORIC ACID HYDROCHLORIC ACID 37%: Alkalis, organic substances, strong oxidants and metals.

10.6. Hazardous decomposition products.

HYDROCHLORIC ACID HYDROCHLORIC ACID 37%: Above decomposition temperature hydrochloric acid fumes may develop.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

HYDROCHLORIC ACID

HYDROCHLORIC ACID 37% - Mixture - Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach - Acute inhalation toxicity, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract - Skin irritation, Mixture causes burns. - Eye irritation, Mixture causes serious eye damage. Risk of blindness! - Specific target organ toxicity, single exposure, Target Organs: Respiratory system, Mixture may cause respiratory irritation.

COBALT (II) CHLORIDE HEXAHYDRATE

Acute oral toxicity, absorption, Symptoms: Tremors, Diarrhoea - Acute inhalation toxicity, absorption, Symptoms: Irritation symptoms in the respiratory tract - Acute dermal toxicity, absorption, Skin irritation, Possible damages: slight irritation - Eye irritation, Possible damages: slight irritation - Sensitisation, May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction - CMR effects, Carcinogenicity: May cause cancer by inhalation - Mutagenicity: Suspected of causing genetic defects - Reproductive toxicity: May damage fertility.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component). LC50 (Inhalation - mists / powders) of the mixture: LD50 (Oral) of the mixture: >2000 mg/kg LD50 (Dermal) of the mixture: Not classified (no significant component). HYDROCHLORIC ACID 4.74 mg/l/1h Rat LC50 (Inhalation). COBALT (II) CHLORIDE HEXAHYDRATE LD50 (Oral). 766 mg/kg Rat Carcinogenicity Assessment: 7647-01-0 HYDROCHLORIC ACID IARC:3 SKIN CORROSION / IRRITATION. Corrosive for the skin.



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 7 / 12

SECTION 11. Toxicological information. />>

SERIOUS EYE DAMAGE / IRRITATION. Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION. Sensitising for the skin.

GERM CELL MUTAGENICITY. Suspected of causing genetic defects.

CARCINOGENICITY. May cause cancer.

REPRODUCTIVE TOXICITY. May damage fertility or the unborn child.

STOT - SINGLE EXPOSURE. Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE. Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD. Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity.

HYDROCHLORIC ACID	
LC50 - for Fish.	282 mg/l/96h
EC50 - for Crustacea.	0.00005 mg/l/48h
COBALT (II) CHLORIDE HEXAHYDRATE LC50 - for Fish. EC50 - for Crustacea. EC10 for Algae / Aquatic Plants. Chronic NOEC for Fish.	1.512 mg/l/96h Oncorhynchus mykiss 6.8 mg/l/48h Ceriodaphnia dubia 0.023 mg/l/72h Pseudokirchnerella subcapitata 0.739 mg/l Pimephales promelas
12.2. Persistence and degradability.	
HYDROCHLORIC ACID	
Solubility in water.	> 10000 mg/l
Biodegradability: Information not available.	
COBALT (II) CHLORIDE HEXAHYDRATE	
Solubility in water.	> 10000 mg/l
Biodegradability: Information not available.	
12.3. Bioaccumulative potential.	
Information not available.	
12.4. Mobility in soil.	
Information not available.	
12.5. Results of PBT and vPvB assessment. Information not available.	
12.6. Other adverse effects.	
HYDROCHLORIC ACID	
	mixtures with water even if diluted. Harmful effect due to pH shift. Discharge into the
environment must be avoided.	mixtures with water even in anales. Harmis cheet due to priomit. Discharge into the
1	



HI96707B - Cal Check® Standard Cuvette B

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA:	3082
ADR / RID:	In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.
IMDG:	In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.
IATA:	In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.
11.2 LIN meanar abing	

14.2. UN proper shipping name.

ADR / RID:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (COBALT II CHLORIDE)
IMDG:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (COBALT II CHLORIDE)
IATA:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (COBALT II CHLORIDE)

14.3. Transport hazard class(es).

ADR / RID:	Class: 9	Label: 9
IMDG:	Class: 9	Label: 9
IATA:	Class: 9	Label: 9

14.4. Packing group.

ADR / RID, IMDG, IATA:

14.5. Environmental hazards.

ADR / RID:	Environmentally Hazardous.
IMDG:	Marine Pollutant.
IATA:	Environmentally Hazardous.

Ш



HI96707B - Cal Check® Standard Cuvette B

SECTION 14. Transport information. ... / >>

14.6. Special precautions for user.

ADR / RID:

IMDG:

IATA:

HIN - Kemler: 90 Special Provision: -EMS: F-A, S-F Cargo: Pass.: Special Instructions: Limited Quantities: 5 L

Limited Quantities: 5 L Maximum quantity: 450 L Maximum quantity: 450 L A97, A158, A197 Tunnel restriction code: (E)

Printed on 4/12/2017

Revision nr.2 Dated 4/12/2017

Page n. 9 / 12

Packaging instructions: 964 Packaging instructions: 964

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

Clean Air Act Section 112(b):

7791-13-1COBALT (II) CHLORIDE HEXAHYDRATE (Cobalt compounds)7647-01-0HYDROCHLORIC ACID

Clean Air Act Section 602 Class I Substances: No component(s) listed.

Clean Air Act Section 602 Class II Substances: No component(s) listed.

Clean Water Act – Priority Pollutants: No component(s) listed.

Clean Water Act – Toxic Pollutants: No component(s) listed.

DEA List I Chemicals (Precursor Chemicals): No component(s) listed.

DEA List II Chemicals (Essential Chemicals): 7647-01-0 HYDROCHLORIC ACID

EPA List of Lists:

 313 Category Code:

 7647-01-0
 HYDROCHLORIC ACID

 7791-13-1
 COBALT (II) CHLORIDE HEXAHYDRATE (Cobalt compounds)

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ: 7647-01-0

HYDROCHLORIC ACID

EPCRA 313 TRI: 7647-01-0

 7647-01-0
 HYDROCHLORIC ACID

 7791-13-1
 COBALT (II) CHLORIDE HEXAHYDRATE (Cobalt compounds)

RCRA Code: No component(s) listed.

CAA 112 (r) RMP TQ: 7647-01-0 HYDROCHLORIC ACID

State Regulations.

Massachussetts:



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 10 / 12

SECTION 15. Regulatory information. ... / >>

7647-01-0	HYDROCHLORIC ACID
Minnesota:	
7647-01-0	HYDROCHLORIC ACID
New Jersey:	
7791-13-1	COBALT (II) CHLORIDE HEXAHYDRATE (Cobalt compounds)
7647-01-0	HYDROCHLORIC ACID
New York:	
7647-01-0	HYDROCHLORIC ACID
Denneydyrenier	
Pennsylvania: 7791-13-1	
	COBALT (II) CHLORIDE HEXAHYDRATE (Cobalt compounds)
7647-01-0	HYDROCHLORIC ACID
California:	
7647-01-0	HYDROCHLORIC ACID
1041-01-0	
Proposition 65:	
This product does	not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.
International Regulations	
None.	
None.	
Substances subject to th	e Rotterdam Convention:
None.	
	e Stockholm Convention:
None.	
Candadian WHMIS.	
Information not ava	ailahle
internation not av	
ECTION 16. C	Other information.
Text of hazard (H)	indications mentioned in section 2-3 of the sheet:
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Carc. 1B	Carcinogenicity, category 1B
Muta. 2	Germ cell mutagenicity, category 2
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1 Aquatic Chronic 1	Hazardous to the aquatic environment, acute toxicity, category 1 Hazardous to the aquatic environment, chronic toxicity, category 1
H290	May be corrosive to metals.
H350	May de concerte to include. May cause cancer.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H360F	May damage fertility.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H334 H317	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 11 / 12

SECTION 16. Other information. />>

- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

- 6 NYCRR part 597

- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified:



HI96707B - Cal Check® Standard Cuvette B

Revision nr.2 Dated 4/12/2017 Printed on 4/12/2017 Page n. 12 / 12

SECTION 16. Other information. .../>>

01.