

REDMARK INDUSTRY SDN. BHD. (935155-U)

KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus, Bandar Baru Sri Petaling, 57000 Kuala Lumpur.

PENANG BRANCH

7206, Mez Floor, Kompleks Perniagaan Pangsapuri Seri Cemerlang, Jalan Kampong Paya, 12200 Butterworth, Penang.

JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman Bestari Indah, 81800 Ulu Tiram, Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor) E: sales@redmarkindustry.com

Uee Series- Portable Hardness Tester Uee910



Functions & Features

- High quality and precision.
- Automatically identify 7 types of Impact devices for special application.
- Freely switch to hardness scales HRB, HRC, HV, HB, HS,HL.
- Direct calibration on HL,HRC,HB.
- PC Software for data transmission, analysis and measurement reports printing.
- Test at any angle, even upside down.
- Large LCD screen with back-light, showing all functions and parameters.
- Upper and lower limit and sound alarm.
- Conversion to tensile strength (U.T.S).
- 3 years warranty and life-long services.

Measuring Materials

• 10 types of metals: steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys, copper and tin alloy, copper, forged steel.



REDMARK INDUSTRY SDN. BHD. (935155-U)

KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus, Bandar Baru Sri Petaling, 57000 Kuala Lumpur.

PENANG BRANCH

7206, Mez Floor, Kompleks Perniagaan Pangsapuri Seri Cemerlang, Jalan Kampong Paya, 12200 Butterworth, Penang.

JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman Bestari Indah, 81800 Ulu Tiram, Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor) E: sales@redmarkindustry.com

Technical Parameters

Model	Uee910
Measuring Range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS,
	(13.5-101.7)HRB
Hardness parameter	HL, HRC,HRB, HS,HB,HV
Accuracy	±6HLD
Memory	600 groups
PC Connection	Available
Battery	2*AA
Operating Temperature	-20℃~+60℃
Dimensions	163×78×33mm
Weight	240g
Standard Configuration	Main unit, Impact Device type D, Calibration block,Small supporting ring, USB cable, Software, Backup accessories(Impact ball*1, Cable*1, Spanner *1), Cleaning brush,Operation manual,Certificate.
Optional Accessories	Optional Impact Devices(D,DC,DL,D+15,G,C,E), Shaped support rings, Testing blocks







