

**KUALA LUMPUR (HQ)**

No. 141-2, Jalan Radin Bagus,  
Bandar Baru Sri Petaling,  
57000 Kuala Lumpur.

**PENANG BRANCH**

7206, Mez Floor, Kompleks  
Perniagaan Pangsapuri Seri  
Cemerlang, Jalan Kampong Paya,  
12200 Butterworth, Penang.

**JOHOR BRANCH**

No.25, Jalan Bestari 24/3, Taman  
Bestari Indah, 81800 Ulu Tiram,  
Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)  
E: sales@redmarkindustry.com

## Uee Series-Portable Hardness Tester Uee912



## Functions & Features

- High quality metal shell
- Precise measuring performance
- Automatically identify 7 types of Impact devices for special application
- Direct calibrate on HL, HRC, HB, and freely switch to 6 different hardness scales
- Test at any angle, even upside down
- Large LCD screen with back-light, showing all functions and parameters
- Conversion to tensile strength (U.T.S)
- PC Software for data transmission, analysis and measurement reports printing
- 3 years warranty and life-long services



**REDMARK INDUSTRY SDN. BHD.** (935155-U)

**KUALA LUMPUR (HQ)**

No. 141-2, Jalan Radin Bagus,  
Bandar Baru Sri Petaling,  
57000 Kuala Lumpur.

**PENANG BRANCH**

7206, Mez Floor, Kompleks  
Perniagaan Pangsapuri Seri  
Cemerlang, Jalan Kampong Paya,  
12200 Butterworth, Penang.

**JOHOR BRANCH**

No.25, Jalan Bestari 24/3, Taman  
Bestari Indah, 81800 Ulu Tiram,  
Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)  
E: sales@redmarkindustry.com

## Measuring Materials

- 10 types of metals: steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys, copper and tin alloy, copper, forged steel.

## Technical Parameters

Model	Uee912
Measuring Range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS, (13.5-101.7)HRB
Hardness parameter	HL, HRC,HRB, HS,HB,HV
Accuracy	±6HLD
Memory	600 groups
PC Connection	Available
Battery	2*AA
Operating Temperature	-20℃~+60℃
Dimensions	130×70×30mm
Weight	300g
Standard Configuration	Main unit, Impact Device type D, Calibration block,Small supporting ring, USB cable, Software, Backup accessories(Impact ball*1, Cable*1, Spanner *1), Cleaning brush, Coin screwdriver, Operation manual,Certificate.
Optional Accessories	Optional Impact Devices(D,DC,DL,D+15,G,C,E), Shaped support rings, Testing blocks



## REDMARK INDUSTRY SDN. BHD. (935155-U)

### KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus,  
Bandar Baru Sri Petaling,  
57000 Kuala Lumpur.

### PENANG BRANCH

7206, Mez Floor, Kompleks  
Perniagaan Pangsapuri Seri  
Cemerlang, Jalan Kampong Paya,  
12200 Butterworth, Penang.

### JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman  
Bestari Indah, 81800 Ulu Tiram,  
Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)  
E: sales@redmarkindustry.com

## Pictures

