

KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus,
Bandar Baru Sri Petaling,
57000 Kuala Lumpur.

PENANG BRANCH

7206, Mez Floor, Kompleks
Perniagaan Pangsapuri Seri
Cemerlang, Jalan Kampong Paya,
12200 Butterworth, Penang.

JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman
Bestari Indah, 81800 Ulu Tiram,
Johor.

T: +603 - 9054 6939 **F:** +603-90545 7939 **M:** +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)
E: sales@redmarkindustry.com

Uee Series - Coating Thickness Gauge Uee922



WARRANTY
3 YEARS



USB



Software



LCD

Functions & Features

- With high quality metal probes and shell.
- Large memory to save 4 types of materials and 1560 testing values.
- Software for PC connection and data transmission, analysis.
- Two measuring methods: continuous and single;
- Two working mode: direct and batch;
- Limit setting function.
- Switch off automatically or manually.
- 3 ways for easy Calibration: by one specimen, two specimens or five specimens to finish calibration..
- Five statistics: Average, Maximum, Minimum, Testing times, Standard deviation.
- Standard delivery with 5 calibration specimens (48.5m、99.8m、249m、513m、1024m)
- 3 years warranty and life-long services



REDMARK INDUSTRY SDN. BHD. (935155-U)

KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus,
Bandar Baru Sri Petaling,
57000 Kuala Lumpur.

PENANG BRANCH

7206, Mez Floor, Kompleks
Perniagaan Pangsapuri Seri
Cemerlang, Jalan Kampong Paya,
12200 Butterworth, Penang.

JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman
Bestari Indah, 81800 Ulu Tiram,
Johor.

T: +603 - 9054 6939 **F:** +603-90545 7939 **M:** +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)
E: sales@redmarkindustry.com

Measuring Materials

- Magnetic Induction (Fe): Measuring the thickness of Non-magnetic coating on magnetic metal substrate, such as aluminum, chromium, copper, zinc, rubber, paint on the base of steel, iron, alloy and magnetic steel .
- Eddy Current (NFe): Measuring the thickness of Non-conductive coating on non-magnetic metal substrate, such as rubber, plastic, paint, oxide on the base of aluminum, copper, zinc, tin.

Technical Parameters

Model No.	Uee922
Measuring principle	Magnetic induction (Fe) & Eddy current (NFe)
Measuring range (µm)	0~1250µm
Probe	Changeable
Shell	Metal
Accuracy	±(2%H+1) µm; H refers to the thickness of testing piece
Minimum resolution (µm)	0.1µm
Min curvature of the min area (mm)	Convex1.5 Concave9
Diameter of the min area (mm)	Φ7
Critical thickness of substrate (mm)	0.5
Memory	1560
Dimensions	130*70*30mm
Power supply	2*AA Alkaline battery
Standard Configuration	Main Machine, probe*1(Fe or NFe), substrate*1(Fe or NFe), software & USB, Calibration specimens*5, Users' Manual, Qualified Certificate, Coin screwdriver, AA battery*2, Packing list, Warranty card



REDMARK INDUSTRY SDN. BHD. (935155-U)

KUALA LUMPUR (HQ)

No. 141-2, Jalan Radin Bagus,
Bandar Baru Sri Petaling,
57000 Kuala Lumpur.

PENANG BRANCH

7206, Mez Floor, Kompleks
Perniagaan Pangsapuri Seri
Cemerlang, Jalan Kampong Paya,
12200 Butterworth, Penang.

JOHOR BRANCH

No.25, Jalan Bestari 24/3, Taman
Bestari Indah, 81800 Ulu Tiram,
Johor.

T: +603 - 9054 6939 F: +603-90545 7939 M: +6012-499 2103 / +6013-399 2103 (Penang) / +6017-228 2103 (Johor)
E: sales@redmarkindustry.com

Optional Accessories

Probes,Specimens

Pictures

