

20W Triple Output Series - with approval



- Universal AC input / full range
 - High reliability
 - Approvals: ETS/LVD/EMC/ CE
 - 100% full load burn-in test
 - Protections: overload/ over voltage/ short circuit
 - V1 is isolated from the other outputs
 - 2 years warranty
 - F602 111 x 78 x 36(mm)

AC input voltage range	85~264VAC (120~370VDC)
Inrush current	cold start, 15A/115V, 30A/230V
Input leakage current	< 0.5mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Load regulation	V ₁ : $\leq \pm 0.5\%$, V ₂ ,V ₃ : $\leq \pm 3\%$ (with regulators); $\leq \pm 6\%$ (without)
Output voltage adjust range	V ₁ : $\pm 5\%$ of rated output voltage
Output overload protection	110~150%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min; I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		R&N	Efficiency
HF20W-TL-A	5V	0.3~2.5A	50mV	
	12V	0.1~0.8A	100mV	71%
	-12V	0.1~0.8A	100mV	
HF20W-TL-B	5V	0.3~2.5A	50mV	
	15V	0.1~0.8A	100mV	72%
	-15V	0.1~0.8A	100mV	
HF20W-TL-C	5V	0.3~2.5A	50mV	
	12V	0.1~0.8A	100mV	69%
	-5V	0.1~1.0A	80mV	

Drawing

