


35W Single Output Open Frame Series

- Universal AC input / full range
- High reliability
- Miniature PCB structure
- Built-in EMI filter
- 107 x 61 x 28(mm)
- Protections: overload/ over voltage/ short circuit
- Free air cooling convection
- 5 years limited warranty



AC input voltage range	85~264VAC (120~370VDC)
Inrush current	cold start, 20A/115V, 40A/230V
Output voltage adjust range	± 10%
Output overload protection	105~150%, hiccup mode, auto recovery
Output over voltage protection	115~150%, shut off, re-power on to recover
Withstand voltage	I/P -O/P:3.0KVAC/1min; I/P-F/G:1.5KVAC/1min O/P-F/G:0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temperature	-20°C~+50°C
Safety standards.....	meet GB4943, UL60950, EN60950
EMC standards.....	meet GB9254, EN55022 classB, EN61000
Connection	2P/ 7.92mm, 4P/ 3.96mm pitch
Weight	0.16kg/pcs

Model	DC Output		Load regul.	R&N	Efficiency
HF35W-SPL-5	5V	7.0A	0.5%	80mV	76%
HF35W-SPL-12	12V	2.9A	0.5%	120mV	81%
HF35W-SPL-24	24V	1.5A	0.5%	150mV	84%
HF35W-SPL-48	48V	0.7A	0.5%	150mV	83%

* 3~48VDC output all available.