

500~700W Single Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: over current/ over voltage/ over temperature/ short circuit
- 1 year warranty
- F650 250 x 160 x 87(mm)

AC input voltage range	170~264VAC
Input frequency	47~63Hz
Inrush current	60A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	± 0.5%
Output voltage adjust range	± 10%
Output over current protection	110~130%, current limiting, auto recovery
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10 ~+50 , 20%~90%RH (non condensing)
Storage temp. & humidity	-20 ~+85 , 20%~95%RH (non condensing)
Safety standards	design refer to GB4943, UL60950, EN60950
EMC standards	design refer to GB9254, EN55022 classA
Cooling method	fan

Model	DC Output		Load regul.	R&N	Efficiency
HF500W-S-12	12V	42A	0.5%	120mV	83%
HF500W-S-13.8	13.8V	35A	0.5%	120mV	84%
HF500W-S-24	24V	21A	0.5%	150mV	85%
HF500W-S-48	48V	11A	0.5%	250mV	87%
HF600W-S-24	24V	25A	0.5%	200mV	85%
HF600W-S-48	48V	13A	0.5%	250mV	87%
HF700W-S-48	48V	15A	0.5%	250mV	87%

Drawing

