

300~400W Dual Output Standard Series



- High reliability, low cost
- Built-in fan speed control
- 100% full load burn-in test
- Protections: overload/ over voltage/ over temperature/ short circuit
- V1 is isolated from the other output
- 5 years limited warranty
- F630 241 x 124 x 65(mm)

AC input voltage range	170~264VAC (210~370VDC)
Inrush current	cold start, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Load regulation	$V_1: \leq \pm 0.5\%, V_2: \leq \pm 3\%$
Output voltage adjust range	$V_1: \pm 5\%$ of rated output voltage
Output overload protection	110~130%, current limiting, auto recovery
Output over voltage protection	115~150%, shut off, re-power on to recover
Withstand voltage	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temperature	-20°C~+50°C
Safety standards	design refer to GB4943, UL60950, EN60950
EMC standards	design refer to GB9254, EN55022 classA
Cooling method	fan

Model	DC Output		R&N	Efficiency
HF300W-D-A	24V	2.0~12.0A	150mV	82%
	5V	0.0~3.00A	100mV	
HF300W-D-B	24V	2.0~11.0A	150mV	83%
	12V	0.0~3.00A	120mV	
HF400W-D-A	24V	2.0~16.0A	150mV	82%
	12V	0.0~3.00A	120mV	
HF400W-D-B	27V	2.0~15.0A	200mV	83%
	12V	0.0~3.00A	120mV	

Drawing

