

30W Triple Output Series - with approval



CE

ETL LVD tested **ETL EMC tested**

- AC input range selected by switch
- High reliability
- Approvals: ETS/LVD/EMC/ CE
- 100% full load burn-in test
- Protections: overload/ over voltage/ short circuit
- V1 is isolated from the other outputs
- 2 years warranty
- F603 129 x 98 x 40(mm)

AC input voltage range	85~132/ 170~264VAC selected by switch
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 0.5mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Load regulation	$V_1: \leq \pm 0.5\%, V_2, V_3: \leq \pm 3\%$ (with regulators); $\leq \pm 6\%$ (without)
Output voltage adjust range	$V_1: \pm 5\%$ of rated output voltage
Output overload protection	110~150%
Output over voltage protection	115~150%
Withstand voltage	I/P-O/P: 3.0KVAC/1min; I/P-F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		R&N	Efficiency
	5V	0.5~3.5A		
HF30W-TF-A	12V	0.1~1.2A	100mV	69%
	-12V	0.1~0.8A	100mV	
	5V	0.5~3.5A	50mV	
HF30W-TF-B	15V	0.1~0.8A	120mV	70%
	-15V	0.0~0.5A	120mV	
	5V	0.5~3.5A	50mV	
HF30W-TF-C	12V	0.1~1.2A	100mV	68%
	-5V	0.0~1.0A	80mV	
	5V	0.5~3.5A	50mV	

Drawing

