


## 150W Triple Output Standard Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- V1 is isolated from the other outputs
- 5 years limited warranty
- F615 199 x 98 x 50(mm)

AC input voltage range .....	170~264VAC (210~370VDC)
Inrush current .....	cold start, 40A/230V
Input leakage current .....	< 0.7mA/ 230VAC
Line regulation (full load) .....	$\leq \pm 0.5\%$
Load regulation .....	V <sub>1</sub> : $\leq \pm 0.5\%$ , V <sub>2</sub> ,V <sub>3</sub> : $\leq \pm 3\%$
Output voltage adjust range .....	V <sub>1</sub> : $\pm 5\%$ of rated output voltage
Output overload protection .....	110~130%
Withstand voltage .....	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time .....	50ms@full load (typical)
Hold up time .....	20ms@full load (typical)
Operating temperature .....	-20°C~+50°C
Safety standards .....	design meet GB4943, UL60950, EN60950
EMC standards .....	design meet GB9254, EN55022 classA EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method .....	convection

Model	DC Output		R&N	Efficiency
	24V	1.0~5.0A		
HF150W-T-A	12V	0.0~2.5A	120mV	78%
	5V	0.0~2.0A	100mV	
	24V	1.0~5.0A	150mV	
HF150W-T-B	12V	0.0~2.5A	120mV	80%
	-12V	0.0~1.5A	120mV	

### Drawing

