

70W DC/DC Series



- High reliability
- Built-in EMI filter
- Protections: overload/ short circuit
- 5 years limited warranty
- F605 160 x 98 x 39(mm)
- F608 146 x 81 x 38(mm) (option)

DC input voltage	24VDC, 48VDC, 110VDC
Line regulation (full load)	$\leq \pm 0.5\%$
Output voltage adjust range	$\pm 10\%$
Output overload protection	105~150%, hiccup mode, auto recovery
Withstand voltage	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Isolation resistance	> 100M Ω @500VDC
Operating temperature	-20°C~+50°C
Safety standards	design refer to LVD
EMC standards	design refer to EN55022, EN61000-4
Cooling method	convection

Model	DC Output	Load regul.	R&N	Efficiency
HF70W-SD**-12	12V	6.0A	0.5%	120mV
HF70W-SD**-15	15V	4.7A	0.5%	120mV
HF70W-SD**-24	24V	3.0A	0.5%	150mV
HF70W-SD**-48	48V	1.5A	0.5%	150mV

**means DC input voltage, such as 24, 48, 110, etc.

Drawing

