100W Triple Output Standard Series

- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- V1 is isolated from the other outputs
- 5 years limited warranty
- F610 199 x 98 x 39(mm)

AC input voltage range	170~264VAC (210~370VDC)
Inrush current	cold start, 40A/230V
Input leakage current	＜0.7mA/ 230VAC
Line regulation (full load)	≤±0.5%
Load regulation	V_1: ≤±0.5%, V_2,V_3: ≤±3%
Output voltage adjust range	V_1: ±5% of rated output voltage
Output overload protection	110~130%
Withstand voltage	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temperature	-10℃~+50℃
Storage temperature	-20℃~+85℃
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	design meet GB9254, EN55022 classA EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		R&N	Efficiency
HF100W-T-A	5V	2.0~12.0A	80mV	73%
	12V	0.0~2.50A	100mV	
	-12V	0.0~1.50A	100mV	
HF100W-T-B	5V	2.0~12.0A	80mV	74%
	15V	0.0~2.50A	100mV	
	-15V	0.0~1.50A	100mV	

Drawing